



## **Technical Data**

**Product: MOBI ALLUMINIUM FINISH** 

#### Description

**MOBI ALUMINIUM PAINT** is a silver paint with superior metallic luster to protect surface from corrosion, discolorations and effect of mild heat. Can be used on pipe lines, chimneys, machine, stream pipes, light poles, storage vessels, bridges & oven doors etc.

### **SURFACE PREPARATION:**

Surface must be free from dust, dirt, grease, oil, heavy shoot, chalk, etc. Remove all old flakes, loose paint to avoid adhesion problem. Scuff with suitable emery paper, and dust off with brush. Apply one coat of MOBI Red Oxide Primer with spray, brush or Roller, allow drying, than apply 3 -4 coats Mobi Aluminum Paint.

**TECHNICAL DATA** 

TYPE : Single Pack.

Flash Point :  $< 21^{\circ}$ C Specific Gravity :  $01 \pm 0.1$ 

Viscosity : 10-16 sec @ ford cup F4

Color : Aluminum Silver

Thinning : Not Required Ready to use

Average Spreading Rate : 140 ~ 170 Sq. Feet per liter per coat.

Drying Time : a. Surface Dry:1 - 2 Hours @ 30°C b. Recoat : 12 Hours @ 30°C

c. Hard Dry : 20 - 24 Hours

Application : Spray ,Brush, Roller

Number of Coats : 3 ~ 4 Coats Finish & Gloss : Smooth, Glossy

Thinner : Mineral Turpentine, White Spirit

Packing : 0.25,0.91, 3.64 Liter

#### **Safety & Handling Precautions:**

- Use protective equipment while application e.g. Apron, Gloves, Protective Glasses and Dust Mask.
- Ensure adequate ventilation during application.
- In case of Eye Splashes, wash with plenty of Fresh Water and consult medical advice.
- > In case of skin contact, wash with plenty of water. In case of skin irritation (Sensitive Skin), obtain medical advice.
- > In case of ingestion, do not induce vomiting. Drink plenty of Milk/Water and immediately consult a physician.
- > Store the product below 40 °C and avoid direct sunlight for a longer period.
- As long as the container is firmly sealed; the material can be kept for 18-Months without deterioration.

Spreading rates are calculated and due allowance for loss and wastage should made. Storage stability 18 months when stored properly in original sealed container at 15-35C. The data is subject to change without notice.

# **NEW MUBEEN PAINT INDUSTRIES (Pvt.) Ltd.**



8-KM Khushab Road, Near Dhrema Sargodha-Pakistan. Ph: +92-48-3710739- Cell: +92-302-8602213 - +92-344-7473646 E-mail: info@mobipaints.com Website: www.mobipaints.com

ISO 9001:2015 CERTIFIED COMPANY