



## Technical Data

Product: MOBI CARE EMULSION

### Description

**Mobi Care Emulsion** Paint is a premium solution that adds a touch of elegance and durability to interior walls. With its smooth application and wide range of vibrant colors, Mobi Care Emulsion Paint transforms any space into a visually stunning and long-lasting environment.

### SURFACE PREPARATION:

Surfaces must be clean, dry, free from masonry salts. Remove all defective or poorly adhering materials by rubbing down using a suitable abrasive paper or stiff brush. Treat any area affected by mould, lichens, algae or moss with bleach. Previously painted surfaces should be thoroughly rubbed down using a suitable abrasive paper and then dust off.

### Filling New Surfaces:

After priming new surfaces with MOBI Interior Water Base Primer / MOBI Oil Base Primer, fill the surface with Mobi Fine Filler/Wall Putty/Care Putty. Please refer to TDS of MOBI Interior Water Base Primer / MOBI Oil Base Primer & Mobi Fine Filler/Wall Putty/Care Putty for correct application procedure and drying time properties.

### Powdery, Dusty Surfaces, Defects, Cracks & Other Surfaces:

Repair minor defects. For large holes & cracks use sand and cement mixture. Allow to dry. Prime the surface with Water Base Primer / MOBI Oil Base Primer and then fill any surface imperfections with the Mobi Fine Filler/Wall Putty/Care Putty. Scuff the surface using suitable abrasive paper and dust off.

### TECHNICAL DATA

#### **Composition (Nominal)**

Pigment	:	Non Lead Pigment
Binder	:	PVA Co-Polymer
Solvent	:	Water

**Solid content by volume (%)** : 65 ± 5 %

**Colors** : As per shade card

**Film Thickness** : Not Applicable

**Drying Time at 25°C** : 1-2 Hours

**Recoat at 25°C** : 3-4 Hours

**Ph** : 8.5 – 9.5

**Pack Viscosity** : 22 – 32 Poise

**Specific Gravity** : 1.50 – 1.62 (Depending Upon Colors)

**No of Coats** : 2 – 3 Coats

## NEW MUBEEN PAINT INDUSTRIES (Pvt.) Ltd.



ISO 9001:2015 CERTIFIED COMPANY



8-KM Khushab Road, Near Dhrema Sargodha-Pakistan.  
Ph: +92-48-3710739- Cell: +92-302-8602213 - +92-344-7473646  
E-mail: [info@mobipaints.com](mailto:info@mobipaints.com) Website: [www.mobipaints.com](http://www.mobipaints.com)



## Technical Data

Product: MOBI CARE EMULSION

### TECHNICAL DATA

<b>Practical Coverage</b>	:	A guide to the practical coverage which can be achieved under normal condition is 120 - 140 Square foot /liter/coat depending upon surface profile
<b>Application</b>	:	Brush,  Roller 
<b>Thinning</b>	:	
<b>Brush or Roller</b>	:	For application thinning should not exceed 2-3 parts of clean water to 4 parts of paint (50-75%).
<b>Cleaning</b>	:	Clean all equipment with water immediately after use.
<b>Finish</b>	:	Smooth Matt Finish
<b>Pack Size</b>	:	3.64 Liter , 14.56 Liter

#### Recommended System: Powdery Surface

- 1coat MOBI MOBI Interior Water Base Primer / MOBI Oil Base Primer
- 2-3 coats Mobi Fine Filler/Wall Putty/Care Putty.
- MOBI Care Emulsion (2 or more coat)

#### Recommended System: Alkaline & New Surface

- 1coat MOBI Interior Water Base Primer / MOBI Oil Base Primer
- 2-3 coats Mobi Fine Filler/Wall Putty/Care Putty.
- MOBI Care Emulsion (2 or more coat)

#### Normal Sound surface previously painted:

- No Primer required.
- Mobi Fine Filler/Wall Putty/Care Putty as and where required.
- MOBI Care Emulsion (2 or more coat)

### Safety & Handling Precautions:

- Use protective equipment while application e.g. Apron, Gloves, Protective Glasses and Dust Mask.
- Ensure adequate ventilation during application.
- In case of Eye Splashes, wash with plenty of Fresh Water and consult medical advice.
- In case of skin contact, wash with plenty of water. In case of skin irritation (Sensitive Skin), obtain medical advice.
- In case of ingestion, do not induce vomiting. Drink plenty of Milk/Water and immediately consult a physician.
- Store the product below 40 °C and avoid direct sunlight for a longer period.
- As long as the container is firmly sealed; the material can be kept for 18-Months without deterioration.

Spreading rates are calculated and due allowance for loss and wastage should made. Storage stability 18 months when stored properly in original sealed container at 15-35C. The data is subject to change without notice.

## NEW MUBEEN PAINT INDUSTRIES (Pvt.) Ltd.



ISO 9001:2015 CERTIFIED COMPANY

8-KM Khushab Road, Near Dhrema Sargodha-Pakistan.  
Ph: +92-48-3710739- Cell: +92-302-8602213 - +92-344-7473646  
E-mail: [info@mobipaints.com](mailto:info@mobipaints.com) Website: [www.mobipaints.com](http://www.mobipaints.com)