



## **Technical Data**

**Product: MOBI CARE PUTTY** 

#### **Description**

MOBI CARE PUTTY (water based) is an economical ready to use filler. It gives a smooth and brilliant white base by filling the pores. It is easy to apply and quick in drying. It gives a smooth finish for topcoat application. MOBI Care Putty is recommended to use only on interior surfaces.

### **SURFACE PREPARATION:**

Allow all new surfaces to dry out completely. Surface must be clean, dry & free of all masonry salts .Remove all defective or poorly adhering materials by rubbing down using a suitable abrasive paper or stiff brush. Treat any area affected by mould, lichens, algae or moss with bleach. Previously painted surfaces should be thoroughly rubbed down using a suitable abrasive paper and then dust off.

#### **New Surfaces:**

Prime new surfaces with 1 coat of MOBI Interior Water Base Primer / MOBI Oil Base Primer. Please refer to TDS of MOBI Interior Water Base Primer / MOBI Oil Base Primer for correct application procedure and drying time properties.

### Powdery, Dusty Surfaces, Defects, Cracks & Other Surfaces:

Repair minor defects. For large holes & cracks use sand and cement mixture. Allow to dry. Prime the surface with MOBI Interior Water Base Primer / MOBI Oil Base Primer before applying MOBI Care Putty.

**TECHNICAL DATA** 

TYPE : Ready to use.

**Composition (Nominal)** 

Pigment : Non Lead Pigment Binder : PVA Co-Polymer

Solvent : Water

Solid content by volume (%) : High solid putty

Film Thickness

**Ph** : 8.5 – 9.5

**Gel Strength** : 150-170 GM/CM3 @30C

Drying Time at 25°C : 2-3 Hours Recoat at 25°C : 4-6 Hours

**Practical Coverage** : A guide to the practical coverage which can be

achieved under normal condition is 40-50 square

Feet /Kg/coat.

# **NEW MUBEEN PAINT INDUSTRIES (Pvt.) Ltd.**



8-KM Khushab Road, Near Dhrema Sargodha-Pakistan. Ph: +92-48-3710739- Cell: +92-302-8602213 - +92-344-7473646

E-mail: info@mobipaints.com Website: www.mobipaints.com





## **Technical Data**

**Product: MOBI CARE PUTTY** 

**TECHNICAL DATA** 

**Application** : Scraper or Putty Applicator

Thinning : Ready to use.

Cleaning : Clean all equipment with water immediately

after use.

Finish : Smooth Matt Finish

Pack Size : ,20 Kg

Recommended System:

Alkaline & New Surface

1coat MOBI Interior Water Base Primer / MOBI Oil Base Primer

- 2-3 coats Mobi Care Putty.
- 2 or more coats any of MOBI interior top coat.

Recommended System:

**Powdery Surface** 

Icoat MOBI Interior Water Base Primer / MOBI Oil Base Primer

- 2-3 coats Mobi Care Putty.
- 2 or more coats any of MOBI interior top coat.

Normal Sound surface previously painted:

- No primer required.
- 2-3 coats MOBI Care Putty where required.
- 2 or more coats any of MOBI interior top coat.

### **Safety & Handling Precautions:**

- Use protective equipment while application e.g. Apron, Gloves, Protective Glasses and Dust Mask.
- > Ensure adequate ventilation during application.
- In case of Eye Splashes, wash with plenty of Fresh Water and consult medical advice.
- In case of skin contact, wash with plenty of water. In case of skin irritation (Sensitive Skin), obtain medical advice.
- > In case of ingestion, do not induce vomiting. Drink plenty of Milk/Water and immediately consult a physician.
- > Store the product below 40 °C and avoid direct sunlight for a longer period.
- > As long as the container is firmly sealed; the material can be kept for 18-Months without deterioration.

Spreading rates are calculated and due allowance for loss and wastage should made. Storage stability 18 months when stored properly in original sealed container at 15-35C. The data is subject to change without notice.

# **NEW MUBEEN PAINT INDUSTRIES (Pvt.) Ltd.**



8-KM Khushab Road, Near Dhrema Sargodha-Pakistan. Ph: +92-48-3710739- Cell: +92-302-8602213 - +92-344-7473646 E-mail: info@mobipaints.com Website: www.mobipaints.com

ISO 9001:2015 CERTIFIED COMPANY