



# Introduction & Product Catalogue

NEW MUBEEN PAINT INDUSTRIES (PVT) LTD.

**MOBI**<sup>®</sup> PAINTS





بِسْمِ اللَّهِ الرَّحْمَنِ الرَّحِيمِ

IN THE NAME OF ALLAH THE MOST MERCIFUL & THE MOST COMPASSIONATE

# Contents

Introduction .....	01
Chairman's Message .....	02
Quality Policy .....	03
Our Core Values, Research & Development .....	04
Mobi Stain Remover .....	05
Mobi Super Emulsion .....	06
Mobi Plastic Emulsion .....	07
Mobi Weather Safe .....	08
Mobi Fine Filler (Water Based) .....	09
Mobi Exterior Fine Filler (Water Based) .....	10
Mobi Exterior Primer (Water Based) .....	11
Mobi Texture Finish .....	12
Mobi Synthetic Enamel .....	13
Mobi Matt Finish (Oil Based) .....	14
Mobi Synthetic Metallic Enamel .....	15
Mobi Undercoat .....	16
Mobi Wall Sealer .....	17
Mobi Red Oxide Primer .....	18
Mobi Synthetic Clear Varnish .....	19
Mobi Wood Gloss Lacquer .....	20
Mobi Wood Sealer .....	21
Mobi Special Thinner .....	22
Mobi Aluminium Finish .....	23
Mobi Primer Filler (Sheesha Putty) .....	24
Mobi Paint Remover.....	25
Mobi Polyurethane Varnish .....	26

# Introduction



Mubeen Paints Industries (MPI), established in 2003, has had over thirteen successful years in paint manufacturing and selling. In the past decades, we have developed an acumen to produce a variety of high quality decorative, industrial and commercial finishes including Synthetic Polyvinyl Distempers, Synthetic Enamels, Matt Finishes & Plastic Emulsions.

MPI is led by a management which is inspired by the vision of its founding chairman; an entrepreneur of the highest calibre who embodies fifteen years of experience in paint manufacturing & selling. Our technical team is staffed with highly qualified technologists and our quality control lab is equipped with all the latest equipment. Our continuous strive for excellence and innovation has made us the only Pakistani paint manufacturer that complies with ISO 9001: 2000 Quality Management System.

Today, 80% of our revenue comes from exports, reconfirming our stature as a quality paint manufacturer. You can buy our products from a network of over 1200 dealers in Pakistan and Abroad.

I also welcome this opportunity to request you to explore our website [www.mobipaints.com](http://www.mobipaints.com). In order to get a better understanding of our products and services. We have learnt a lot from our customers therefore, it is extremely important for us to keep hearing from you on our performance at every step of product development, delivery and application. We are highly indebted to you for your continued support; hence, Helping us setting higher standards in our Customer Services. Our sales staff will be happy to share more information, should you have any questions or suggestions. For more Information Contact us at [info@mobipaints.com](mailto:info@mobipaints.com).

## Our Vision

To be the manufacturer of decorative paints in Pakistan that offers the greatest value for the need of both professional and home consumers. To be a brand that is the most desired and respected by dealers and recognized for quality by consumers while offering afford ability to the widest range of coating solutions. To be a leader in sales and services of professional painting solutions and be a source of pride for our country in the international market.

## Mission

We are a company dedicated to the manufacturing of paints and coatings of the highest quality. We strive to:

- Satisfy our customers by offering quality products and services that leave little to be desired on their end.
- Generate wealth to fuel company's growth and staff development. Thus leading to a more well- rounded company that sets the industrial benchmark ever so higher.
- Develop innovative products and solutions that provide the adequate resource for individuals and professionals to manifest their dream paint job



## Chairman's Message:



### **"In the name of ALLAH, the Most Gracious and the Most Merciful"**

Mobi Paints started its operation in 2003 as small scale paints manufacturer centered on quality. Since then, by the grace of Allah, we have gone from strength to strength. what was initially an intra-city venture is now one of the leading paint brand in the country that has now set success its eyes on the global frontier.

I believe that the company's success lies in our objective to never compromise on quality. Our paints are manufactured in compliance with national and international standards by a team of worthy chemists in a world class plant. An independent quality control department further ensures that each batch that is sent to the market confronts to the strict standards we have set for ourselves.

Our Quest for quality does not stop there. Mobi Paints's R&D department also plays its hand in the continual improvement and innovation of our products, to give you the best and most enduring paint finish. In short, I am grateful to Almighty ALLAH who has bestowed me with the best professionals, and I am thankful to you, the customer, for your unwavering confidence in Mobi Paints.

A handwritten signature in dark ink, appearing to read "Tasleem Raza", with a horizontal line drawn underneath it.

Tasleem Raza  
C.E.O. (Mobi Group)

Mubeen Paint Industries (MPI) is dedicated to a strict quality policy that ensures our products and services fully meet the requirements of our customers while sustaining the environment at all times. The goal of MPI is to maximize value for our customers, business partners and community by remaining committed to the implementation of supporting managerial and business operational systems essential to realising this goal. We believe in the concept of consumers, applicators and supplier working together in pursuing this policy and in continually striving for improvements in the product and service quality. Our quality policy is based on 3 fundamental principles:

- 1- Ensuring that we fully identify and conform to the needs of our customers and community in which we are working.
- 2- Looking at our product manufacturing and service provision processes, identifying the potential for errors and taking the necessary action to eliminate them.
- 3- Confirming that every one of our employees understand how to do their job right.

To ensure that the policy is successfully implemented, our staff will be responsible for identifying customer requirements, and ensuring that the correct procedures are followed to meet those requirements. Objectives needed to ensure that the requirements of this policy are met and that continual improvement is maintained in line with the spirit of the policy, will be set, determined and monitored at Management Review. The quality policy principles and objectives will be communicated and available to staff at all times. Training will be an integral part of the strategy to achieve the objectives. With this Policy we are committed to operating our Company under the disciplines and controls of a Quality Management System conforming to the International Standard ISO 9001 : 2000, planned and developed jointly with our other management functions.

We are all committed to operating continuously to this standard and we will maintain the necessary Quality Approvals consistent with our customer requirements.

MPI will constantly review and improve on our products and services to ensure that tasks are completed in the most cost effective and timely manner for the benefit of all our customers. We shall ensure that all our personnel understand and fully implement our Company's policies and objectives and are able to perform their duties effectively through an on-going training and development program.



# Our Core Values



## ► Professionalism

Utilize specialized expertise, systems and routines to carry out best Practices.

## ► Innovation

Benefit from technology and innovation to develop better products and efficient processes.

## ► Integrity

Characterize our efforts with honesty and loyalty towards the company, the customers & ourselves.

## ► People

Attract, develop, train and retain the talent, take care of our people and create a challenging environment for them to work in.

## ► Care

Taking care of the society and the people around us by playing our part as a socially responsible corporate entity.

## ■ Research & Development

Research and Development is responsible for the launch of new products. Our R & D department constantly researches and keeps up to date with competitive analysis. This exercise gives us an edge over the competitors. We invest heavily in research and development and pursue every opportunity to produce even more economical but high performance products.

# Mobi Stain Remover



## ■ TECHNICAL INFORMATION

PACK VISCOSITY	4-8 Poise @ 25 °C
SPECIFIC GRAVITY	1.28~1.34 (Depends on the Colors)
PH	8.5 ~ 9.5
DRYING TIME	02 ~ 04 Hours (Depends on Temperature and Humidity)
COVERAGE	10 ~13 m <sup>2</sup> / L / Coat (Depends on Surface Porosity)
NUMBER OF COATS	02 ~ 03
SOLVENT / CLEANER	Water

## ■ SURFACE PREPARATION

Surface must be free from dust, dirt, grease, oil, heavy shoot, chalk, etc. Remove all Old, flaking, loose paint to avoid adhesion problem.

### ■ New Surface Preparation

After Plastering, allow the surface to dry for minimum 12~15 weeks. Moisture contents must not exceed 15% in the plaster before application.

After the wall is dry, apply one thin coat of MOBI Water Base Primer and allow dry for 02 ~ 03 Hours.

Apply Fine Filler with suitable scrappers.

Apply 2-3 coats of Mobi Stain Remover with recommended intervals of time.

### ■ Old Surface Preparation

Wire-brush the surface to remove flaking, loose Paint.

Scuff with suitable sand paper.

Dust of the powder with dry brush.

Apply one thin coat of MOBI Water Base Wall Primer and allow drying.

Apply Fine Filler with suitable scrappers.

Apply 2-3 Coats of Mobi Stain Remover with recommended time intervals.

## ■ APPLICATION

For best results, apply 03 ~ 04 coats (Depends on surface porosity) of MOBI Stain Remover with recommended time intervals.

Do not apply "Thick Coats" to avoid brush marks.

## ■ SAFETY AND HANDLING PRECAUTIONS

Use protective equipment while application e.g. Apron, Gloves, Protective Glasses and Dust Mask.

Ensure adequate ventilation during application.

In case of Eye Splashes, wash with plenty of Fresh Water and consult medical advice.

In case of skin contact, wash with plenty of water. In case of skin irritation (Sensitive Skin), obtain medical advice.

In case of ingestion, do not induce vomiting. Drink plenty of Milk/Water and immediately consult a physician.

Store the product below 40 °C and avoid direct sunlight for a longer period.

As long as the container is firmly sealed; the material can be kept for 18-Months without deterioration.





## Mobi Stain Remover

MOBI STAIN REMOVER is a specially formulated acrylic emulsion with outstanding best quality for interior surfaces application. It is low VOC interior premium paint specially formulated to repel the stains like, ketchup, coffee, juice, and handprints etc. Stains can be removed without damaging the paint film. It has excellent brush ability, flow, leveling, washability, smooth finish, color fastness, beautiful low sheen and long lasting durability. MOBI Stain remover offering higher hiding and maximum protection masonry surfaces including brickwork plaster cement and wall boards.



# Mobi Super Emulsion



## ■ TECHNICAL INFORMATION

<b>PACK VISCOSITY</b>	22-32 Poise @ 25 °C
<b>SPECIFIC GRAVITY</b>	1.5~1.62 (Depends on the Colors)
<b>PH</b>	8.5 ~ 9.5
<b>DRYING TIME</b>	02 ~ 03 Hours (Depends on Temperature and Humidity)
<b>COVERAGE</b>	12 ~14 m <sup>2</sup> / L / Coat (Depends on Surface Porosity)
<b>NUMBER OF COATS</b>	02 ~ 03
<b>SOLVENT / CLEANER</b>	Water

## ■ SURFACE PREPARATION

Surface must be free from dust, dirt, grease, oil, heavy shoot, chalk, etc. Remove all Old, flaking, loose paint to avoid adhesion problem.

### ■ New Surface Preparation

After Plastering, allow the surface to dry for minimum 12~15 weeks. Moisture contents must not exceed 15% in the plaster before application.

After the wall is dry, apply one thin coat of MOBI Interior Water Base Primer / MOBI Oil Base Primer and allow drying.

Apply 2-3 coats of Mobi Fine Filler and allow drying.

Apply 2-3 coats of MOBI Super Emulsion with recommended time intervals.

### ■ Old Surface Preparation

Wire-brush the surface to remove flaking, loose Paint.

Scuff with suitable sand paper.

Dust of the powder with dry brush.

Apply one thin coat of MOBI Interior Water Base Wall Primer or MOBI Oil Base Primer and allow drying.

Apply 2-3 Coats of Mobi Fine Filler and allow drying.

Apply 2-3 coats of MOBI Super Emulsion with recommended time intervals.

## ■ APPLICATION

For best results, apply 03 ~ 04 coats (Depends on surface porosity) of MOBI Super Emulsion with recommended time intervals.

Do not apply "Thick Coats" to avoid brush marks.

## ■ SAFETY AND HANDLING PRECAUTIONS

Use protective equipment while application e.g. Apron, Gloves, Protective Glasses and Dust Mask.

Ensure adequate ventilation during application.

In case of Eye Splashes, wash with plenty of Fresh Water and consult medical advice.

In case of skin contact, wash with plenty of water. In case of skin irritation (Sensitive Skin), obtain medical advice.

In case of ingestion, do not induce vomiting. Drink plenty of Milk/Water and immediately consult a physician.

Store the product below 40 °C and avoid direct sunlight for a longer period.

As long as the container is firmly sealed; the material can be kept for 18-Months without deterioration.





## Mobi Super Emulsion

MOBI SUPER EMULSION is a PVA Co-Polymer based good quality Emulsion for all normal interior masonry surfaces including brick work, plaster, cement rendering and wall boards. A blend of selective pigments, extenders and additives in special Emulsion make it good quality emulsion. It has good adhesion on suitably prepared surfaces with better hiding and coverage. MOBI Super Emulsion is recommended only on interior surfaces.



# Mobi Plastic Emulsion



## ■ TECHNICAL INFORMATION

PACK VISCOSITY	16-22 Poise @ 25 °C
SPECIFIC GRAVITY	1.38~1.45 (Depends on the Colors)
PH	8.5 ~ 9.5
DRYING TIME	02 ~ 03 Hours (Depends on Temperature and Humidity)
COVERAGE	12 ~13 m <sup>2</sup> / L / Coat (Depends on Surface Porosity)
NUMBER OF COATS	03 ~ 04
SOLVENT / CLEANER	Water

## ■ SURFACE PREPARATION

Surface must be free from dust, dirt, grease, oil, heavy shoot, chalk, etc. Remove all Old, flaking, loose paint to avoid adhesion problem.

### ■ New Surface Preparation

After Plastering, allow the surface to dry for minimum 12~15 weeks. Moisture contents must not exceed 15% in the plaster before application.

After the wall is dry, apply one thin coat of MOBI Water Base Primer / MOBI Oil Base Primer and allow drying.

Apply 2-3 coats of Mobi Fine Filler and allow drying.

Apply 2-3 coats of MOBI Plastic Emulsion with recommended time intervals.

### ■ Old Surface Preparation

Wire-brush the surface to remove flaking, loose Paint.

Scuff with suitable sand paper.

Dust of the powder with dry brush.

Apply one thin coat of MOBI Water Base Wall Primer or MOBI Oil Base Primer and allow drying.

Apply 2-3 Coats of Mobi Fine Filler and allow drying.

Apply 2-3 coats of MOBI Plastic Emulsion with recommended time intervals.

## ■ APPLICATION

For best results, apply 03 ~ 04 coats (Depends on surface porosity) of MOBI Plastic Emulsion with recommended time intervals.

Do not apply "Thick Coats" to avoid brush marks.

## ■ SAFETY AND HANDLING PRECAUTIONS

Use protective equipment while application e.g. Apron, Gloves, Protective Glasses and Dust Mask.

Ensure adequate ventilation during application.

In case of Eye Splashes, wash with plenty of Fresh Water and consult medical advice.

In case of skin contact, wash with plenty of water. In case of skin irritation (Sensitive Skin), obtain medical advice.

In case of ingestion, do not induce vomiting. Drink plenty of Milk/Water and immediately consult a physician.

Store the product below 40 °C and avoid direct sunlight for a longer period.





## Mobi Plastic Emulsion

MOBI PLASTIC EMULSION is good quality Emulsion for all normal interior masonry surfaces including brick work, plaster, cement rendering and wall boards. A blend of selective pigments, extenders and additives in special Emulsion make it good quality emulsion. It has good adhesion on suitably prepared surfaces with better hiding and coverage. MOBI Plastic Emulsion is recommended only on interior surfaces.



# Mobi Weather Safe



## ■ TECHNICAL INFORMATION

PACK VISCOSITY	16-22 Poise @ 25 °C
SPECIFIC GRAVITY	1.36~1.46 (Depends on the Colors)
PH	8.5 ~ 9.5
DRYING TIME	02 ~ 03 Hours (Depends on Temperature and Humidity)
COVERAGE	13 ~15 m <sup>2</sup> / L / Coat (Depends on Surface Porosity)
NUMBER OF COATS	03 ~ 04
SOLVENT / CLEANER	Water

## ■ SURFACE PREPARATION

Surface must be free from dust, dirt, grease, oil, heavy shoot, chalk, etc. Remove all Old, flaking, loose paint to avoid adhesion problem.

### ■ New Surface Preparation

After Plastering, allow the surface to dry for minimum 12~15 weeks. Moisture contents must not exceed 15% in the plaster before application.

After the wall is dry, apply one thin coat of MOBI Exterior Water Base Primer and allow dry for 02~03 Hours.

Apply 2-3 coats of Mobi Weather Safe with recommended intervals of time.

### ■ Old Surface Preparation

Wire-brush the surface to remove flaking, loose Paint.

Scuff with suitable sand paper.

Dust of the powder with dry brush.

Apply one thin coat of MOBI Exterior Water Base Wall Primer and allow drying.

Apply 2-3 Coats of Mobi Weather Safe with recommended time intervals.

## ■ APPLICATION

For best results, apply 03 ~ 04 coats (Depends on surface porosity) of MOBI Weather Safe with recommended time intervals.

Do not apply "Thick Coats" to avoid brush marks.

## ■ SAFETY AND HANDLING PRECAUTIONS

Use protective equipment while application e.g. Apron, Gloves, Protective Glasses and Dust Mask.

Ensure adequate ventilation during application.

In case of Eye Splashes, wash with plenty of Fresh Water and consult medical advice.

In case of skin contact, wash with plenty of water. In case of skin irritation (Sensitive Skin), obtain medical advice.

In case of ingestion, do not induce vomiting. Drink plenty of Milk/Water and immediately consult a physician.

Store the product below 40 °C and avoid direct sunlight for a longer period.

As long as the container is firmly sealed; the material can be kept for 18-Months without deterioration.



## Mobi Weather Safe

MOBI WEATHER SAFE is a specially formulated emulsion with outstanding best quality for exterior surfaces application. It gives tough & durable exterior coating suitable for all weather conditions. A blend of selective pigment, extenders and additives make it a brand top of its class. It has color lock technology. MOBI Weather Safe is recommended to use on Exterior surface



# Mobi Fine Filler (Water Based)



## ■ TECHNICAL INFORMATION

APPEARANCE	White Paste
PACK VISCOSITY	180-220 GMCM @ Gel Strength @ 30 °C
SPECIFIC GRAVITY	1.56~1.62
PH	8.5 ~ 9.5
DRYING TIME	02 ~ 03 Hours (Depends on Temperature and Humidity)
COVERAGE	04 ~05 m2 / Kg / Coat (Depends on Surface Porosity)
NUMBER OF COATS	02 ~ 03
SOLVENT / CLEANER	Water

## ■ SURFACE PREPARATION

Surface must be free from dust, dirt, grease, oil, heavy shoot, chalk, etc. Remove all Old, flaking, loose paint to avoid adhesion problem.

### ■ New Surface Preparation

After Plastering, allow the surface to dry for minimum 12~15 weeks. Moisture contents must not exceed 15% in the plaster before application.

After the wall is dry, apply one thin coat of MOBI Water Base Primer / Mobi Oil Base Wall Primer and allow drying.

Apply MOBI Fine Filler with scrapper.

### ■ Old Surface Preparation

Wire-brush the surface to remove flaking, loose Paint.

Scuff with suitable sand paper.

Dust of the powder with dry brush.

Apply one thin coat of MOBI Oil Base Wall Primer / MOBI Water Base Primer and allow drying.

Apply MOBI Fine Filler with suitable scrapper.

## ■ APPLICATION

For best results, apply 3 ~ 4 coats (Depends on surface porosity) of MOBI Fine Filler with recommended time intervals.

After proper drying, rub down with suitable sand paper to smooth the surface.

## ■ SAFETY AND HANDLING PRECAUTIONS

Use protective equipment while application e.g. Apron, Gloves, Protective Glasses and Dust Mask.

Ensure adequate ventilation during application.

In case of Eye Splashes, wash with plenty of Fresh Water and consult medical advice.

In case of skin contact, wash with plenty of water. In case of skin irritation (Sensitive Skin), obtain medical advice.

In case of ingestion, do not induce vomiting. Drink plenty of Milk/Water and immediately consult a physician.

Store the product below 40 °C and avoid direct sunlight for a longer period.

As long as the container is firmly sealed; the material can be kept for 12-Months without deterioration.



## Mobi Fine Filler (Water Based)

MOBI FINE FILLER water based putty is a specialized product used to seal the pores, smooth the surface by filling the porous, uneven spots and cracks. It is brilliant white in color, easy to apply and quick in drying. Its excellent filling properties give a smooth finish for topcoat application. MOBI Fine filler is recommended to use only on interior surfaces.



# Mobi Exterior Fine Filler (Water Based)



## ■ TECHNICAL INFORMATION

PACK VISCOSITY	160-180 GMCM @ Gel Strength @ 30 °C
SPECIFIC GRAVITY	1.50 ~ 1.60
PH	8.5 ~ 9.5
COLOR	White
DRYING TIME	02 ~ 03 Hours (Depends on Temperature and Humidity)
RECOATING TIME	4 Hours Minimum (Depends on Temperature and Humidity)
COVERAGE	05 ~07 m <sup>2</sup> / Kg / Coat (Depends on Surface Porosity)
SOLVENT / CLEANER	Water

## ■ SURFACE PREPARATION

Surface must be free from dust, dirt, grease, oil, heavy shoot, chalk, mildew etc. Remove all old, flaking, loose paint to avoid adhesion problem.

### ■ New Surface Preparation

After Plastering, allow the surface to dry for minimum 12~15 weeks. Moisture contents must not exceed 15% in the plaster before application.

After the wall is dry, apply one thin coat of MOBI Exterior Primer and allow dry.

Apply the Mobi Exterior Fine Filler with suitable scrappers.

### ■ Old Surface Preparation

Wire-brush the surface to remove flaking, loose Paint.

Apply one thin coat of Mobi Exterior Primer and allow dry.

Apply the Mobi Exterior Fine Filler with suitable scrapper.

## ■ APPLICATION

For best results, apply 1~2 coats (Depends on surface porosity) of MOBI Exterior Fine Filler with 06 ~ 08 Hours interval.

Do not dilute the product with water. It is available in "Ready to Use" packing.

## ■ SAFETY AND HANDLING PRECAUTIONS

Use protective equipment while application e.g. Apron, Gloves, Protective Glasses and Dust Mask.

Ensure adequate ventilation during application.

In case of Eye Splashes, wash with plenty of Fresh Water and consult medical advice.

In case of skin contact, wash with plenty of water. In case of skin irritation (Sensitive Skin), obtain medical advice.

In case of ingestion, do not induce vomiting. Drink plenty of Milk/Water and immediately consult a physician.

As long as the container is firmly sealed; the material can be kept for 18-Months without deterioration





## Mobi Exterior Fine Filler (Water Based)

MOBI EXTERIOR FINE FILLER (water based) Filler is a high quality acrylic based fine filler for all types of exterior masonry surfaces such as brickwork, plaster and cement. It is ready to use and easy to apply. It gives smooth finish for top coat. Mobi Exterior Fine Filler is recommended to use only exterior surfaces



# Mobi Exterior Primer (Water Based)



## ■ TECHNICAL INFORMATION

PACK VISCOSITY	18-22 Poise @ 25 °C
SPECIFIC GRAVITY	1.46~1.52
PH	8.5 ~ 9.5
DRYING TIME	02 ~ 03 Hours (Depends on Temperature and Humidity)
COVERAGE	16 ~18 m <sup>2</sup> / L / Coat (Depends on Surface Porosity)
NUMBER OF COATS	01 ~ 02
SOLVENT / CLEANER	Water

## ■ SURFACE PREPARATION

Surface must be free from dust, dirt, grease, oil, heavy shoot, chalk, etc. Remove all Old, flaking, loose paint to avoid adhesion problem.

### ■ New Surface Preparation

After Plastering, allow the surface to dry for minimum 12~15 weeks. Moisture contents must not exceed 15% in the plaster before application.

After the wall is dry, apply one thin coat of MOBI Exterior Water Base Primer and allow dry for 02 ~ 03 Hours.

### ■ Old Surface Preparation

Wire-brush the surface to remove flaking, loose Paint.

Scuff with suitable sand paper.

Dust of the powder with dry brush.

Apply one thin coat of MOBI Exterior Water Base Primer with brush or Roller with recommended number of coats and allow dry 02 ~ 03 Hours.

## ■ APPLICATION

For best results, apply 01 ~ 02 coats (Depends on surface porosity) of MOBI Exterior Water Base Primer with recommended time intervals.

Do not apply "Thick Coats" of the primer.

## ■ SAFETY AND HANDLING PRECAUTIONS

Use protective equipment while application e.g. Apron, Gloves, Protective Glasses and Dust Mask.

Ensure adequate ventilation during application.

In case of Eye Splashes, wash with plenty of Fresh Water and consult medical advice.

In case of skin contact, wash with plenty of water. In case of skin irritation (Sensitive Skin), obtain medical advice.

In case of ingestion, do not induce vomiting. Drink plenty of Milk/Water and immediately consult a physician.

Store the product below 40 °C and avoid direct sunlight for a longer period.

As long as the container is firmly sealed; the material can be kept for 18-Months without deterioration.



## Mobi Exterior Primer (Water Based)

MOBI EXTERIOR PRIMER is acrylic copolymer base alkali resistant primer with excellent quality for interior and exterior surfaces application. It has good salt and moisture resistant.





# Mobi Texture Finish



## ■ TECHNICAL INFORMATION

APPEARANCE	White Paste
PACK VISCOSITY	80-100 GMCM @ Gel Strength @ 30 °C
SPECIFIC GRAVITY	1.54~1.58
PH	8.5 ~ 9.5
DRYING TIME	02 ~ 03 Hours (Depends on Temperature and Humidity)
COVERAGE	1.0 ~1.5 m <sup>2</sup> / Kg / Coat (Depends on Surface Porosity)
NUMBER OF COATS	01 ~ 02
SOLVENT / CLEANER	Water

## ■ SURFACE PREPARATION

Surface must be free from dust, dirt, grease, oil, heavy shoot, chalk, etc. Remove all Old, flaking, loose paint to avoid adhesion problem.

### ■ New Surface Preparation

After Plastering, allow the surface to dry for minimum 12~15 weeks. Moisture contents must not exceed 15% in the plaster before application.

After the wall is dry, apply one thin coat of MOBI Water Base Primer / Mobi Oil Base Wall Primer and allow drying.

Apply MOBI Texture finish with Pattern Roller.

### ■ Old Surface Preparation

Wire-brush the surface to remove flaking, loose Paint.

Scuff with suitable sand paper.

Dust of the powder with dry brush.

Apply one thin coat of MOBI Oil Base Wall Primer / MOBI Water Base Primer and allow drying.

Apply MOBI Texture Finish with Pattern Roller.

## ■ APPLICATION

For best results, apply 1 ~ 2 coats (Depends on surface porosity) of MOBI Texture Finish with recommended time intervals.

## ■ SAFETY AND HANDLING PRECAUTIONS

Use protective equipment while application e.g. Apron, Gloves, Protective Glasses and Dust Mask.

Ensure adequate ventilation during application.

In case of Eye Splashes, wash with plenty of Fresh Water and consult medical advice.

In case of skin contact, wash with plenty of water. In case of skin irritation (Sensitive Skin), obtain medical advice.

In case of ingestion, do not induce vomiting. Drink plenty of Milk/Water and immediately consult a physician.

Store the product below 40 °C and avoid direct sunlight for a longer period.

As long as the container is firmly sealed; the material can be kept for 12-Months without deterioration.



## Mobi Texture Finish

MOBI TEXTURE FINISH is a high quality water base paste for producing different kinds of eye catching textural effects, which are followed by a final coat of Mobi Super Emulsion or Matt Finish. MOBI texture is recommended to use only on interior surfaces.



# Mobi Synthetic Enamel



## ■ TECHNICAL INFORMATION

VISCOSITY	420 ~ 480 F4 Cup @ 25 °C
SPECIFIC GRAVITY	0.98~1.10 (Depending on colors)
COVERAGE	14 ~17 m <sup>2</sup> / L / Coat (Depends on Surface Porosity)
NUMBER OF COATS	02 ~03 Coats Recommended
APPLICATION	Brush/ Roller/ Spray Gun
DRYING TIME	<b>Surface Dry:</b> 01 ~ 02 Hours (Depends on Environment Temperature) <b>Hard Dry:</b> 20 ~ 24 Hours (Depends on Environment Temperature)
RE-COATING TIME	12 Hours (Minimum)
SOLVENT / CLEANER	Mineral Turpentine/ White Spirit

## ■ SURFACE PREPARATION

### New Surface Preparation

Surface must be free from dust, dirt, grease, oil, heavy shoot, chalk, etc. Remove all Old, flaking, loose paint to avoid adhesion problem.

Scuff with suitable emery paper, and dust off with brush.

Apply one coat of MOBI Red Oxide Primer/ Mobi Wall Primer with brush or Roller; allow drying, than apply Mobi Synthetic Enamel with recommended number of coats.

### Old Surface Preparation

Wire-brush the surface to remove loose Paint.

Scuff with suitable emery paper, and dust off with brush.

Apply one coat of MOBI Red Oxide Primer/ Mobi Wall Primer with brush or Roller; allow drying, than apply Mobi Synthetic Enamel with recommended number of coats.

## ■ SAFETY AND HANDLING PRECAUTIONS

Use protective equipment while application e.g. Apron, Gloves, Protective Glasses and Dust Mask.

Ensure adequate ventilation during application.

In case of Eye Splashes, wash with plenty of Fresh Water and consult medical advice.

In case of skin contact, wash with plenty of water. In case of skin irritation (Sensitive Skin), obtain medical advice.

In case of ingestion, do not induce vomiting. Drink plenty of Milk/Water and immediately consult a physician.

Store the product below 40 °C and avoid direct sunlight for a longer period.

As long as the container is firmly sealed; the material can be kept for 18-Months without deterioration.



## Mobi Synthetic Enamel

MOBI All Purpose Synthetic Enamel is high quality enamel that has no comparison because of its long lasting finish and durability. MOBI Synthetic Enamel is designed to be applied on Ferrous as well as Non-Ferrous substrate. It is suitable for all types of interior and exterior, wood and metal surfaces.





# Mobi Matt Finish (Oil Based)



## ■ TECHNICAL INFORMATION

SPECIFIC GRAVITY	1.20 ~ 1.32
PACK VISCOSITY	14-20 Poise @ 25 °C
GRIND	30-35 $\mu$
GLOSS	16 ~ 20 %@60° SHEEN Head
COLOR	Assorted Shades Available
SOLVENT / CLEANER	MTT/ White Spirit
COVERING	14 ~ 17 m <sup>2</sup> / Liter / Coat (Depends on Surface Porosity)
NUMBER OF COATS	2-3 Coats (Recommended)
DRYING TIME	<b>Surface Dry:</b> 02 ~ 03 Hours (Depends on Environment Temperature) <b>Hard Dry:</b> 16 ~ 24 Hours (Depends on Environment Temperature)
RE-COATING TIME	16 Hours (Minimum)

## ■ SURFACE PREPARATION

Surface must be free from dust, dirt, oil, grease, rust and any loose, flaking matter.

For wall use MOBI Wall Primer, use MOBI Fine Filler/ Mobi Wall Putty to smooth surface before applying MOBI Matt Enamel.

## ■ STORAGE AND HANDLING PRECAUTIONS

Keep away from Heat and Spark Sources

Keep under shed, away from direct sunlight

Keep the containers closed in storage

Never breath the Dust, Mist, Gas, Vapors from the container

Use the paint in ventilation

Store below 30 °C for best performance

As long as container is firmly sealed and stored under recommended storage conditions, product can be used within 6-Months of manufacturing date.



## Mobi Matt Finish (Oil Based)

MOBI MATT FINISH is an excellent quality paint which protects the surface from water and its vapours. It is washable that's why is maintain the beauty of walls, roofs, Wood, Metal, chipboards and hardboards specially bathroom, kitchen and corridors for years.



# Mobi Synthetic Metallic Enamel



## ■ TECHNICAL INFORMATION

VISCOSITY	420 ~ 480 F4 Cup @ 25 °C
SPECIFIC GRAVITY	0.96~1.10 (Depending on colors)
COVERAGE	14 ~17 m <sup>2</sup> / L / Coat (Depends on Surface Porosity)
NUMBER OF COATS	02 ~03 Coats Recommended
APPLICATION	Spray Gun/Roller/Brush
DRYING TIME	<b>Surface Dry:</b> 01 ~ 02 Hours (Depends on Environment Temperature) <b>Hard Dry:</b> 20 ~ 24 Hours (Depends on Environment Temperature)
RE-COATING TIME	12 Hours (Minimum)
SOLVENT / CLEANER	Mineral Turpentine/ White Spirit

## ■ SURFACE PREPARATION

### New Surface Preparation

Surface must be free from dust, dirt, grease, oil, heavy shoot, chalk, etc. Remove all Old, flaking, loose paint to avoid adhesion problem.

Scuff with suitable emery paper, and dust off with brush.

Apply one coat of MOBI Red Oxide Primer/ Mobi Wall Primer with brush or Roller; allow drying, than apply Mobi Synthetic Metallic Enamel with recommended number of coats.

### Old Surface Preparation

Wire-brush the surface to remove loose Paint.

Scuff with suitable emery paper, and dust off with brush.

Apply one coat of MOBI Red Oxide Primer/ Mobi Wall Primer with brush or Roller; allow drying, than apply Mobi Synthetic Metallic Enamel with recommended number of coats.

## ■ SAFETY AND HANDLING PRECAUTIONS

Use protective equipment while application e.g. Apron, Gloves, Protective Glasses and Dust Mask.

Ensure adequate ventilation during application.

In case of Eye Splashes, wash with plenty of Fresh Water and consult medical advice.

In case of skin contact, wash with plenty of water. In case of skin irritation (Sensitive Skin), obtain medical advice.

In case of ingestion, do not induce vomiting. Drink plenty of Milk/Water and immediately consult a physician.

Store the product below 40 °C and avoid direct sunlight for a longer period.





## Mobi Synthetic Metallic Enamel

MOBI MATT FINISH is an excellent quality paint which protects the surface from water and its vapours. It is washable that's why it maintains the beauty of walls, roofs, Wood, Metal, chipboards and hardboards specially bathroom, kitchen and corridors for years.





# Mobi Undercoat



## ■ TECHNICAL INFORMATION

SPECIFIC GRAVITY	1.4 ~ 1.46
PACK VISCOSITY	16.0 ~ 20 POISE @ 25 °C
APPLICATION METHOD	Spray, Brush, Roller
SOLVENT / CLEANER	Turpentine Oil
GRIND	25-30 $\mu$
COVERING	14 ~ 17 m <sup>2</sup> / Liter / Coat
NUMBER OF COATS	1-2 Coats (Recommended)
DRYING TIME	<b>Surface Dry:</b> 01 ~ 02 Hours (Depends on Environment Temperature) <b>Hard Dry:</b> 16 ~ 18 Hours (Depends on Environment Temperature)
RE-COATING TIME	16 Hours (Minimum)
COLOR	White

## ■ SURFACE PREPARATION

### New Surface Preparation

Surface must be free from dust, dirt, oil, grease, rust and any loose, flaking matter.

Scuff with suitable emery paper, and dust off with brush.

For Wall, apply one coat of MOBI Synthetic Undercoat with brush or Roller; allow drying.

### Old Surface Preparation

Wire-brush the surface to remove loose Paint.

Scuff with suitable emery paper, and dust off with brush.

Apply one coat of MOBI Synthetic Undercoat with brush or Roller; allow drying.

## ■ STORAGE AND HANDLING PRECAUTIONS

Keep away from Heat and Spark Sources

Keep under shed, away from direct sunlight

Keep the containers closed in storage

Never breath the Dust, Mist, Gas, Vapors from the container

Use the paint in ventilation

Store below 30 °C for best performance

As long as container is firmly sealed and stored under recommended storage conditions.

As long as the container is firmly sealed; the material can be kept for 18-Months without deterioration.



## Mobi Undercoat

MOBI SYNTHETIC UNDERCOAT is top quality undercoat made from highest quality resin and pigment with carefully selected fillers. Mobi Wall Sealer is specially formulated to protect and seal the surface. It reduces damaged produced by alkali and salts. It gives smooth finish and better coverage to topcoat. It can be apply on all interior surfaces.

# Mobi Wall Sealer



## ■ TECHNICAL INFORMATION

SPECIFIC GRAVITY	1.4 ~ 1.46
PACK VISCOSITY	16.0 ~ 20 POISE @ 25 °C
APPLICATION METHOD	Spray, Brush, Roller
SOLVENT / CLEANER	Turpentine Oil
GRIND	25-30 $\mu$
COVERING	14 ~ 17 m <sup>2</sup> / Liter / Coat
NUMBER OF COATS	1-2 Coats (Recommended)
DRYING TIME	<b>Surface Dry:</b> 01 ~ 02 Hours (Depends on Environment Temperature) <b>Hard Dry:</b> 16 ~ 18 Hours (Depends on Environment Temperature)
RE-COATING TIME	16 Hours (Minimum)
COLOR	White

## ■ SURFACE PREPARATION

### **New Surface Preparation**

Surface must be free from dust, dirt, oil, grease, rust and any loose, flaking matter.

Scuff with suitable emery paper, and dust off with brush.

For Wall, apply one coat of MOBI Wall Sealer with brush or Roller; allow drying.

### **Old Surface Preparation**

Wire-brush the surface to remove loose Paint.

Scuff with suitable emery paper, and dust off with brush.

Apply one coat of MOBI Wall Sealer with brush or Roller; allow drying.

## ■ STORAGE AND HANDLING PRECAUTIONS

Keep away from Heat and Spark Sources

Keep under shed, away from direct sunlight

Keep the containers closed in storage

Never breath the Dust, Mist, Gas, Vapors from the container

Use the paint in ventilation

Store below 30 °C for best performance

As long as container is firmly sealed and stored under recommended storage conditions.

As long as the container is firmly sealed; the material can be kept for 18-Months without deterioration.





## Mobi Wall Sealer

MOBI WALL SEALER is top quality wall sealer made from highest quality resin and pigment with carefully selected fillers. Mobi Wall Sealer is specially formulated to protect and seal the surface. It reduces damaged produced by alkali and salts. It gives smooth finish and better coverage to topcoat. It can be apply on all interior surfaces.



# Mobi Red Oxide Primer



## ■ TECHNICAL INFORMATION

<b>SPECIFIC GRAVITY</b>	1.33 ~ 1.41
<b>PACK VISCOSITY</b>	16.0 ~ 22.0 POISE @ 25 °C
<b>APPLICATION METHOD</b>	Spray, Brush, Roller
<b>SOLVENT / CLEANER</b>	Turpentine Oil
<b>COVERING</b>	12 ~ 18 m <sup>2</sup> / Liter / Coat
<b>NUMBER OF COATS</b>	1-2 Coats (Recommended)
<b>DRYING TIME</b>	<b>Surface Dry:</b> 01 ~ 02 Hours (Depends on Environment Temperature) <b>Hard Dry:</b> 16 ~ 18 Hours (Depends on Environment Temperature)
<b>RE-COATING TIME</b>	16 Hours (Minimum)
<b>COLOR</b>	Red Oxide

## ■ SURFACE PREPARATION

### New Surface Preparation

Surface must be free from dust, dirt, oil, grease, rust and any loose, flaking matter.

Ferrous metals to be treated with Phosphate Conversion Coating for best performance.

Scuff with suitable emery paper, and dust off with brush.

Apply one coat of MOBI Red Oxide Primer with brush or Roller; allow drying, than apply Mobi Synthetic Enamel with recommended number of coats.

### Old Surface Preparation

Wire-brush the surface to remove loose Paint.

Scuff with suitable emery paper, and dust off with brush.

Apply one coat of MOBI Red Oxide Primer with brush or Roller; allow drying, than apply Mobi Synthetic Enamel with recommended number of coats.

## ■ STORAGE AND HANDLING PRECAUTIONS

Keep away from Heat and Spark Sources

Keep under shed, away from direct sunlight

Keep the containers closed in storage

Never breath the Dust, Mist, Gas, Vapors from the container

Use the paint in ventilation

Store below 30 °C for best performance

As long as container is firmly sealed and stored under recommended storage conditions.

As long as the container is firmly sealed; the material can be kept for 18-Months without deterioration.



## Mobi Red Oxide Primer

MOBI RED OXIDE PRIMER is used in industries and homes to protect the ferrous surface from corrosion. Due to its excellent decorative as well as protective qualities, it is also recommended to be used on a variety of Industrial Appliances and Machines. MOBI Red Oxide Primer is composed of a blend of specially designed Resin with non-corrosion pigment and inert extenders which impart its exclusive properties of corrosion resistance, adhesion and colorfastness coupled with mild chemical and good environment resistance.





# Mobi Synthetic Clear Varnish



## ■ TECHNICAL INFORMATION

Viscosity	240 ~ 300 F4 Cup @ 25 °C
Specific Gravity	0.96~1.0
Number of Coats	01 ~02 Coats Recommended
Application	Spray Gun/Roller/Brush
Drying Time	<b>Surface Dry:</b> 01 ~ 02 Hours (Depends on Environment Temperature) <b>Hard Dry:</b> 20 ~ 24 Hours (Depends on Environment Temperature)
Re-Coating Time	12 Hours (Minimum)
Solvent / Cleaner	Mineral Turpentine/ White Spirit

## ■ SURFACE PREPARATION

### New Surface Preparation

Surface must be free from dust, dirt, grease, oil, heavy shoot, chalk, etc. Remove all Old, flaking, loose paint to avoid adhesion problem.

Scuff with suitable emery paper, and dust off with brush.

Apply one coat of MOBI Red Oxide Primer, Apply Mobi Synthetic Enamel with brush or Roller; allow drying, than apply Mobi Synthetic clear varnish with recommended number of coats

### Old Surface Preparation

Wire-brush the surface to remove loose Paint.

Scuff with suitable emery paper, and dust off with brush.

Apply one coat of MOBI Red Oxide Primer, Apply Mobi Synthetic Enamel with brush or Roller; allow drying, than apply Mobi Synthetic clear varnish with recommended number of coats.

## ■ SAFETY AND HANDLING PRECAUTIONS

Use protective equipment while application e.g. Apron, Gloves, Protective Glasses and Dust Mask.

Ensure adequate ventilation during application.

In case of Eye Splashes, wash with plenty of Fresh Water and consult medical advice.

In case of skin contact, wash with plenty of water. In case of skin irritation (Sensitive Skin), obtain medical advice.

In case of ingestion, do not induce vomiting. Drink plenty of Milk/Water and immediately consult a physician.

Store the product below 40 °C and avoid direct sunlight for a longer period.



## Mobi Synthetic Clear Varnish

MOBI SYNTHETIC CLEAR VARNISH is based on selected resin and solvent mixture. It is a protective coating against humidity, steam lubricating oil mild acids and alkalis. It is suitable for all types of interior and exterior, wood and metal surfaces.



# Mobi Wood Gloss Lacquer



## ■ TECHNICAL INFORMATION

VISCOSITY	30 ~ 36 F4 Cup @ 25 °C
SPECIFIC GRAVITY	0.94~0.98
COVERAGE	10 ~11 m2 / L / Coat
NUMBER OF COATS	02 ~03 Coats Recommended
APPLICATION	Roller/ Spray Gun
DRYING TIME	<b>Surface Dry:</b> 15~20 Min(Depends on Environment Temperature) <b>Hard Dry:</b> 3 ~ 4 Hours (Depends on Environment Temperature)
RE-COATING TIME	30 Min (Minimum)
SOLVENT / CLEANER	Mobi Wood Finish Thinner

## ■ SURFACE PREPARATION

### New Surface Preparation

Surface must be free from dust, dirt, grease, oil, heavy shoot, chalk, etc. Remove all Old, flaking, loose paint to avoid adhesion problem.

Scuff with suitable emery paper, and dust off with brush.

Apply 2-3 coats of MOBI Wood Sealer with spray, or Roller; allow drying, than apply Mobi Wood Gloss Lacquer with recommended number of coats.

### Old Surface Preparation

Wire-brush the surface to remove loose Paint.

Scuff with suitable emery paper, and dust off with brush.

Apply 2-3 coats of MOBI Wood Sealer with spray, or Roller; allow drying, than apply Mobi Wood Gloss Lacquer with recommended number of coats.

## ■ SAFETY AND HANDLING PRECAUTIONS

Use protective equipment while application e.g. Apron, Gloves, Protective Glasses and Dust Mask.

Ensure adequate ventilation during application.

In case of Eye Splashes, wash with plenty of Fresh Water and consult medical advice.

In case of skin contact, wash with plenty of water. In case of skin irritation (Sensitive Skin), obtain medical advice.

In case of ingestion, do not induce vomiting. Drink plenty of Milk/Water and immediately consult a physician.

Store the product below 40 °C and avoid direct sunlight for a longer period.





## Mobi Wood Gloss Lacquer

MOBI WOOD GLOSS LACQUER is especially formulated for application on wooden surface, which provide clear finish with excellent adhesion and durability. Its transparent finish provides a clear and flexible finish thus enhancing natural beauty of the wood. It's tough and hard film provides excellent resistance to water, tea and beverages stains.



# Mobi Wood Sealer

## ■ TECHNICAL INFORMATION

VISCOSITY	30 ~ 36 F4 Cup @ 25 °C
SPECIFIC GRAVITY	0.94~0.98
COVERAGE	10 ~11 m2 / L / Coat
NUMBER OF COATS	02 ~03 Coats Recommended
APPLICATION	Roller/ Spray Gun
DRYING TIME	<b>Surface Dry:</b> 15~20 Min(Depends on Environment Temperature) <b>Hard Dry:</b> 3 ~ 4 Hours (Depends on Environment Temperature)
RE-COATING TIME	30 Min (Minimum)
SOLVENT / CLEANER	Mobi Wood Finish Thinner

## ■ SURFACE PREPARATION

### New Surface Preparation

Surface must be free from dust, dirt, grease, oil, heavy shoot, chalk, etc. Remove all Old, flaking, loose paint to avoid adhesion problem.

Scuff with suitable emery paper, and dust off with brush.

Apply 2-3 coats of MOBI Wood Sealer with spray, or Roller; allow drying, than apply Mobi wood topcoats as per requirement.

### Old Surface Preparation

Wire-brush the surface to remove loose Paint.

Scuff with suitable emery paper, and dust off with brush.

Apply 2-3 coats of MOBI Wood Sealer with spray, or Roller; allow drying, than apply Mobi wood topcoats as per requirement.

## ■ SAFETY AND HANDLING PRECAUTIONS

Use protective equipment while application e.g. Apron, Gloves, Protective Glasses and Dust Mask.

Ensure adequate ventilation during application.

In case of Eye Splashes, wash with plenty of Fresh Water and consult medical advice.

In case of skin contact, wash with plenty of water. In case of skin irritation (Sensitive Skin), obtain medical advice.

In case of ingestion, do not induce vomiting. Drink plenty of Milk/Water and immediately consult a physician.

Store the product below 40 °C and avoid direct sunlight for a longer period.





## Mobi Wood Sealer

MOBI WOOD SEALER is an NC based premium quality sealer for wood and wood care products. It is an ideal sealer to fill surface imperfections of all kinds of wooden furniture and fixtures. It penetrates into the pores of wood and prevents sinkage of topcoat to allow good hold out.



# Mobi Wood Special Thinner



## ■ TECHNICAL INFORMATION

Specific Gravity	0.8~0.84
Pack Size	0.91L, 3.64L
Color	Water White Clear
Composition	Mixture of Aromatic And Aliphatic Hydrocarbons
Thinning Ratio	Mobi Wood Sealer 1:1 (By Volume) Mobi Gloss Lacquer 1:1 (By Volume) Mobi Matt Lacquer 1:1 (By Volume)





## Mobi Wood Special Thinner

MOBI WOOD THINNER is especially designed with a blend of aromatic and aliphatic hydrocarbons to make it a perfect thinner for any nitrocellulose based paint or lacquer. Its balanced formula provides excellent solvent blend for application in all seasons. It provides excellent finish.



# Mobi Aluminium Finish

## ■ TECHNICAL INFORMATION

<b>VISCOSITY</b>	10 ~ 16 F4 Cup @ 25 °C
<b>SPECIFIC GRAVITY</b>	0.96~1.10 (Depending on colors)
<b>COVERAGE</b>	14 ~17 m2 / L / Coat (Depends on Surface Porosity)
<b>NUMBER OF COATS</b>	03 ~04 Coats Recommended
<b>APPLICATION</b>	Brush/ Roller/ Spray Gun
<b>DRYING TIME</b>	<b>Surface Dry:</b> 01 ~ 02 Hours (Depends on Environment Temperature) <b>Hard Dry:</b> 20 ~ 24 Hours (Depends on Environment Temperature)
<b>RE-COATING TIME</b>	12 Hours (Minimum)
<b>SOLVENT / CLEANER</b>	Mineral Turpentine/ White Spirit

## ■ SURFACE PREPARATION

### **New Surface Preparation**

Surface must be free from dust, dirt, grease, oil, heavy shoot, chalk, etc. Remove all Old, flaking, loose paint to avoid adhesion problem.

Scuff with suitable emery paper, and dust off with brush.

Apply one coat of MOBI Red Oxide Primer with spray, brush or Roller; allow drying, than apply Mobi Aluminium Paint with recommended number of coats.

### **Old Surface Preparation**

Wire-brush the surface to remove loose Paint.

Scuff with suitable emery paper, and dust off with brush.

Apply one coat of MOBI Red Oxide Primer with spray, brush or Roller; allow drying, than apply Mobi Aluminium Paint with recommended number of coats.

## ■ SAFETY AND HANDLING PRECAUTIONS

Use protective equipment while application e.g. Apron, Gloves, Protective Glasses and Dust Mask.

Ensure adequate ventilation during application.

In case of Eye Splashes, wash with plenty of Fresh Water and consult medical advice.

In case of skin contact, wash with plenty of water. In case of skin irritation (Sensitive Skin), obtain medical advice.

In case of ingestion, do not induce vomiting. Drink plenty of Milk/Water and immediately consult a physician.

Store the product below 40 °C and avoid direct sunlight for a longer period.





## Mobi Aluminium Finish

MOBI ALUMINIUM PAINT is a silver paint with superior metallic luster to protect surface from corrosion, discolorations and effect of mild heat. Can be used on pipe lines, chimneys, machine, stream pipes, light poles, storage vessels, bridges & oven doors etc.





# Mobi Primer Filler (Sheesha Putty)

## ■ TECHNICAL INFORMATION

APPEARANCE	White Paste
PACK VISCOSITY	140-160 GMCM @ Gel Strength @ 30 °C
SPECIFIC GRAVITY	1.56~1.62
PH	8.5 ~ 9.5
DRYING TIME	02 ~ 03 Hours (Depends on Temperature and Humidity)
COVERAGE	04 ~05 m <sup>2</sup> / Kg / Coat (Depends on Surface Porosity)
NUMBER OF COATS	02 ~ 03
SOLVENT / CLEANER	Water

## ■ SURFACE PREPARATION

Surface must be free from dust, dirt, grease, oil, heavy shoot, chalk, etc. Remove all Old, flaking, loose paint to avoid adhesion problem.

### **New Surface Preparation**

After Plastering, allow the surface to dry for minimum 12~15 weeks. Moisture contents must not exceed 15% in the plaster before application.

After the wall is dry, apply one thin coat of MOBI Water Base Primer / Mobi Oil Base Wall Primer and allow drying.

Apply Mobi Primer Filler Sheesha Putty with scrapper.

### **Old Surface Preparation**

Wire-brush the surface to remove flaking, loose Paint.

Scuff with suitable sand paper.

Dust of the powder with dry brush.

Apply one thin coat of MOBI Oil Base Wall Primer / MOBI Water Base Primer and allow drying.

Apply MOBI Primer Filler Sheesha Putty with suitable scrapper.

## ■ APPLICATION

For best results, apply 3 ~ 4 coats (Depends on surface porosity) of MOBI Primer Filler Sheesha Putty with recommended time intervals.

After proper drying, rub down with suitable sand paper to smooth the surface.

## ■ SAFETY AND HANDLING PRECAUTIONS

Use protective equipment while application e.g. Apron, Gloves, Protective Glasses and Dust Mask.

Ensure adequate ventilation during application.

In case of Eye Splashes, wash with plenty of Fresh Water and consult medical advice.

In case of skin contact, wash with plenty of water. In case of skin irritation (Sensitive Skin), obtain medical advice.

In case of ingestion, do not induce vomiting. Drink plenty of Milk/Water and immediately consult a physician.

Store the product below 40 °C and avoid direct sunlight for a longer period.

As long as the container is firmly sealed; the material can be kept for 12-Months without deterioration.



## Mobi Primer Filler (Sheesha Putty)

MOBI PRIMER FILLER SHEESHA PUTTY is a high quality ready to use filler for all types of interior masonry surfaces. It is brilliant white in color, easy to apply and quick in drying. Its excellent filling properties give a smooth finish for topcoat application. MOBI Primer Filler is not recommended for exterior use.

# Mobi Paint Remover

## ■ TECHNICAL INFORMATION

VISCOSITY	Viscous Liquid
COVERAGE	07 ~09 m <sup>2</sup> / L / Coat (Depends on Surface Porosity)
APPLICATION	Brush/Roller
DRYING TIME	Will react with underlying paint within 5-15 minutes.
SOLVENT / CLEANER	Clean Water

## ■ METHOD OF USE

Apply a generous coating of Paint Remover with a soft brush ensuring that the surface is evenly and completely covered. Allow time for Remover to penetrate. The time will vary with the types and number of coating to be removed. Normally 5 to 10 minutes will be found adequate but for 2 pack coatings or Stoving Enamels, an interval up to 30 minutes may be required. One useful method, after applying paint Remover is to place a sheet of newspaper over the wet surface; this helps reduce evaporation and assists penetration. When the paint has assumed a wrinkled or blistered appearance strip of softened film with a scraper or on ornamental surfaces with scrubbing brush and water. Where several coats exist it may be necessary to repeat the process. After removal of the old paint film, the surface should be thoroughly washed with fresh cold water taking care to get the old paint remover out of any hidden areas, edges, comers, nuts, bolts, mouldings, etc.

## ■ STORAGE AND HANDLING PRECAUTIONS

Use protective equipment while application e.g. Apron, Gloves, Protective Glasses and Dust Mask.

Ensure adequate ventilation during application.


In case of Eye Splashes, wash with plenty of Fresh Water and consult medical advice.

In case of skin contact, wash with plenty of water. In case of skin irritation (Sensitive Skin), obtain medical advice.

In case of ingestion, do not induce vomiting. Drink plenty of Milk/Water and immediately consult a physician.

Store the product below 40 °C and avoid direct sunlight for a longer period.





## Mobi Paint Remover

MOBI PAINT REMOVER is premier quality paint remover which can be used on all kind of surfaces such as acrylic, varnish, enamel, auto paint and NC coating.



# Mobi Polyurethane Varnish

## ■ TECHNICAL INFORMATION

VISCOSITY	80 ~ 100 F4 Cup @ 30 °C
SPECIFIC GRAVITY	0.96~1.0
NUMBER OF COATS	01 ~02 Coats Recommended
APPLICATION	Spray Gun/Roller/Brush
DRYING TIME	<b>Surface Dry:</b> 01 ~ 02 Hours (Depends on Environment Temperature) <b>Hard Dry:</b> 20 ~ 24 Hours (Depends on Environment Temperature)
RE-COATING TIME	12 Hours (Minimum)
SOLVENT / CLEANER	Mineral Turpentine/ White Spirit

## ■ SURFACE PREPARATION

### New Surface Preparation

Surface must be free from dust, dirt, grease, oil, heavy shoot, chalk, etc. Remove all Old, flaking, loose paint to avoid adhesion problem.

Scuff wooden surface with suitable emery paper, and dust off.

Apply one coat of MOBI POLYURETHANE Clear varnish with brush, roller or spray.

For better results apply 2nd thinned coat of PU Varnish with recommended interval of time.

### Old Surface Preparation

Suitable for exterior / interior wooden surfaces or where very high gloss, very hard and abrasion resistant clear finish is required.

Previously painted surfaces should be thoroughly rubbed down using a suitable abrasive paper and then dusted off.

A thinned coat of MOBI PU clear varnish applies.

## ■ SAFETY AND HANDLING PRECAUTIONS

Use protective equipment while application e.g. Apron, Gloves, Protective Glasses and Dust Mask.

Ensure adequate ventilation during application.

In case of Eye Splashes, wash with plenty of Fresh Water and consult medical advice.

In case of skin contact, wash with plenty of water. In case of skin irritation (Sensitive Skin), obtain medical advice.

In case of ingestion, do not induce vomiting. Drink plenty of Milk/Water and immediately consult a physician.

Store the product below 40 °C and avoid direct sunlight for a longer period.





## Mobi Polyurethane Varnish

MOBI PU Clear Varnish is PU modified alkyd based, pigment free clear varnish, which is suitable for all types of interior & exterior wooden and metal surfaces. It provides ultimate protection and durability to Wood and metal surfaces. It is designed to produce a flexible and clear film to protect the substrate against environmental concerns such as ultraviolet light, dirt and moisture. The cured coating is resistant to polymer degradation and yellowing.







## New Mubeen Paint Industries (Pvt) Ltd.

**Head Office:** Ph: 048-3710739, 3717213, +92-302+8602213

**Distributor of Afghanistan:** Mohammad Shoaib Rahan LTD.

**Kabul Office:** +93-777122166,785959031

@ info@mobipaints.com

instagram/mobipaints

f facebook/mobipaints

www.mobipaints.com