



Technical Data

Product: MOBI EXTERIOR FINE FILLER

Description

MOBI EXTERIOR FINE FILLER (water based) Filler is a high quality acrylic based fine filler for all types of exterior masonry surfaces such as brickwork, plaster and cement. It is ready to use and easy to apply. It gives smooth finish for top coat. Mobi Exterior Fine Filler is recommended to use only exterior surfaces.

SURFACE PREPARATION:

Allow all new surfaces to dry out completely. Surface must be clean, dry & free of all masonry salts. Remove all defective or poorly adhering materials by rubbing down using a suitable abrasive paper or stiff brush. Treat any area affected by mould, lichens, algae or moss with bleach. Previously painted surfaces should be thoroughly rubbed down using a suitable abrasive paper and then dust off.

New Surfaces:

Prime new surfaces with 1 coat of MOBI Exterior Wall Primer. Please refer to TDS of MOBI Exterior Wall Primer for correct application procedure and drying time properties.

Powdery, Dusty Surfaces, Defects, Cracks & Other Surfaces:

Repair minor defects. For large holes & cracks use sand and cement mixture. Allow to dry. Prime the surface with MOBI Exterior Wall Primer before applying MOBI Exterior Fine Filler.

TECHNICAL DATA

TYPE	:	Ready to use.
Composition (Nominal)		
Pigment	:	Non Lead Pigment
Binder	:	Acrylic Co-Polymer
Solvent	:	Water
Solid content by volume (%)	:	70 ± 5
Film Thickness		
Ph	:	8.5 – 9.5
Gel Strength	:	150 - 170 GM/CM3 @30C
Drying Time at 25°C	:	2-3 Hours
Recoat at 25°C	:	4-6 Hours
Practical Coverage	:	A guide to the practical coverage which can be achieved under normal condition is 50-70 square Feet /Kg/coat.

NEW MUBEEN PAINT INDUSTRIES (Pvt.) Ltd.



ISO 9001:2015 CERTIFIED COMPANY


8-KM Khushab Road, Near Dhrema Sargodha-Pakistan.
Ph: +92-48-3710739- Cell: +92-302-8602213 - +92-344-7473646
E-mail: info@mobipaints.com Website: www.mobipaints.com



Technical Data

Product: MOBI EXTERIOR FINE FILLER

TECHNICAL DATA

Application	:	Scrapper or Putty Applicator 
Thinning	:	Ready to use.
Cleaning	:	Clean all equipment with water immediately after use.
Finish	:	Smooth Matt Finish
Pack Size	:	5 Kg, 20 Kg

Recommended System:

Alkaline & New Surface

- 1 coat MOBI Exterior Wall Primer
- 1 coat Mobi Exterior Fine Filler.
- 2 or more coats any of MOBI Exterior top coat.

Recommended System:

Powdery Surface

- 1 coat MOBI Exterior Wall Primer
- 1 coat Mobi Exterior Fine Filler.
- 2 or more coats any of MOBI Exterior top coat.

Normal Sound surface previously

painted:

- 1 coat MOBI Exterior Wall Primer
- 1 coat Mobi Exterior Fine Filler where required.
- 2 or more coats any of MOBI Exterior top coat.

Safety & Handling Precautions:

- Use protective equipment while application e.g. Apron, Gloves, Protective Glasses and Dust Mask.
- Ensure adequate ventilation during application.
- In case of Eye Splashes, wash with plenty of Fresh Water and consult medical advice.
- In case of skin contact, wash with plenty of water. In case of skin irritation (Sensitive Skin), obtain medical advice.
- In case of ingestion, do not induce vomiting. Drink plenty of Milk/Water and immediately consult a physician.
- Store the product below 40 °C and avoid direct sunlight for a longer period.
- As long as the container is firmly sealed; the material can be kept for 18-Months without deterioration.

Spreading rates are calculated and due allowance for loss and wastage should made. Storage stability 18 months when stored properly in original sealed container at 15-35C. The data is subject to change without notice.

NEW MUBEEN PAINT INDUSTRIES (Pvt.) Ltd.



ISO 9001:2015 CERTIFIED COMPANY

8-KM Khushab Road, Near Dhrema Sargodha-Pakistan.
Ph: +92-48-3710739- Cell: +92-302-8602213 - +92-344-7473646
E-mail: info@mobipaints.com Website: www.mobipaints.com