



Technical Data

Product: MOBI EXTERIOR PRIMER

Description

MOBI Exterior Primer is a high quality acrylic based alkali resistant primer for masonry surfaces. It is ideal for all types of exterior surfaces such as plaster brickwork or cement rendering. It is an excellent sealing primer, which provides good adhesion both for the surface and top coat.

New Surface:

New surfaces must be clean, dry and free from masonry salts. Remove all defective or poorly adhering material by rubbing down using a suitable abrasive paper or stiff brush and dust off. Treat any area affected by mould, lichens, algae or moss with bleach. Now prime the new surface with MOBI Exterior Primer. Let it dry for 2-3 hours and then smooth the surface with Mobi Exterior Fine Filler.

Repaint for Sound Surface:

Remove all defective or poorly adhering material by rubbing down using a suitable abrasive paper and dust off. Prime and fill the surface as described above.

Powdery, Dusty Surfaces, Defects, Cracks & Other Surfaces:

Repair minor defects. For large holes and cracks, use sand and cement mixture. Allow it to dry. Now prime the surface with MOBI Exterior Primer and then fills the surface imperfections with Mobi Exterior Fine Filler as described above

TECHNICAL DATA

Composition (Nominal)

Pigment	:	Non Lead Pigment
Binder	:	Acrylic Co-Polymer
Solvent	:	Water

Solid content by volume (%)	:	65 ± 5 %
Colors	:	White
Film Thickness	:	Not Applicable
Drying Time at 25°C	:	1-2 Hours
Recoat at 25°C	:	3-4 Hours
Ph	:	8.5 – 9.5
Pack Viscosity	:	18 - 22 Poise
Specific Gravity	:	1.45 ± 0.05
No of Coats	:	1 - 2 Coats

NEW MUBEEN PAINT INDUSTRIES (Pvt.) Ltd.





8-KM Khushab Road, Near Dhrema Sargodha-Pakistan.
Ph: +92-48-3710739- Cell: +92-302-8602213 - +92-344-7473646
E-mail: info@mobipaints.com Website: www.mobipaints.com



Technical Data

Product: MOBI EXTERIOR PRIMER

TECHNICAL DATA

Practical Coverage	:	A guide to the practical coverage which can be achieved under normal condition is 100 - 130 Square foot /liter/coat depending upon surface profile.
Application	:	Brush,  Roller 
Thinning	:	
Brush or Roller	:	For application thinning should not exceed 2-3 parts of clean water to 4 parts of paint (50-75%).
Cleaning	:	Clean all equipment with water immediately after use.
Finish	:	Smooth Matt Finish
Pack Size	:	3.64 Liter , 14.56 Liter

Recommended System: Powdery Surface

- 1-2 coat MOBI Exterior Primer
- 1-2 coats MOBI Exterior Fine Filler.
- 2 or more coats of MOBI Finishing Coat Exterior

Recommended System: Alkaline & New Surface

- 1-2 coat MOBI Exterior Primer
- 1-2 coats MOBI Exterior fine Filler.
- 2 or more coats of MOBI Finishing Coat Exterior

Normal Sound surface previously painted:

- 1-2 coat MOBI Exterior Primer if required.
- 1-2 coats MOBI Exterior Fine Filler.
- 2 or more coats of MOBI Finishing Coat Exterior

Safety & Handling Precautions:

- Use protective equipment while application e.g. Apron, Gloves, Protective Glasses and Dust Mask.
- Ensure adequate ventilation during application.
- In case of Eye Splashes, wash with plenty of Fresh Water and consult medical advice.
- In case of skin contact, wash with plenty of water. In case of skin irritation (Sensitive Skin), obtain medical advice.
- In case of ingestion, do not induce vomiting. Drink plenty of Milk/Water and immediately consult a physician.
- Store the product below 40 °C and avoid direct sunlight for a longer period.
- As long as the container is firmly sealed; the material can be kept for 18-Months without deterioration.

Spreading rates are calculated and due allowance for loss and wastage should made. Storage stability 18 months when stored properly in original sealed container at 15-35C. The data is subject to change without notice.

NEW MUBEEN PAINT INDUSTRIES (Pvt.) Ltd.



8-KM Khushab Road, Near Dhrema Sargodha-Pakistan.
Ph: +92-48-3710739- Cell: +92-302-8602213 - +92-344-7473646
E-mail: info@mobipaints.com Website: www.mobipaints.com