



## Technical Data

**Product: MOBI MATT ENAMEL**

### Description

MOBI MATT FINISH is an excellent quality paint which protects the surface from water and its vapors. It is washable paint which maintain the beauty of walls, roofs, Wood, Metal, chipboards and hardboards specially bathroom, kitchen and corridors for years.

### SURFACE PREPARATION:

Surfaces must be free from dust, dirt, grease, oil, heavy shoot or chalk. Remove all defective or poorly adhering materials by rubbing down using a suitable abrasive paper or stiff brush.

### Metal Surface:

After priming new surfaces with MOBI Red Oxide Primer or Wash primer for nonferrous surface, fill the surface where required with Steel Putty. Please refer to TDS of Mobi Red Oxide Primer for correct application procedure and drying time properties.

### Wooden Surface:

Scuff of the surface with suitable abrasive paper than prime the surface with MOBI Undercoat White and then fill any surface imperfections with Putty. Scuff the surface using suitable abrasive paper and dust off.

### TECHNICAL DATA

#### **Composition (Nominal)**

Pigment	:	Non Lead Pigment
Binder	:	Alkyd
Solvent	:	MTT, Kerosene Oil, White Spirit

Volume solids	:	50 ± 10 %
Colors	:	All Colors from shade card.
Film Thickness	:	Dry : 35 ± 5 microns.
Pack Viscosity	:	18 – 22 Poise
Specific Gravity	:	1.36 ± 0.1 Depending upon colors
Gloss	:	Maximum 10 Gu
Drying Time at 25°C	:	5-6 Hours
Recoat at 25°C	:	16 Hours
Practical Coverage	:	A guide to the practical coverage which can be achieved under normal condition is 140 -170 Square foot /liter/coat.

## NEW MUBEEN PAINT INDUSTRIES (Pvt.) Ltd.



8-KM Khushab Road, Near Dhrema Sargodha-Pakistan.  
Ph: +92-48-3710739- Cell: +92-302-8602213 - +92-344-7473646  
E-mail: [info@mobipaints.com](mailto:info@mobipaints.com) Website: [www.mobipaints.com](http://www.mobipaints.com)



## Technical Data

Product: MOBI MATT ENAMEL

### TECHNICAL DATA

Application

:

Brush,



Roller



Spray



Thinning

:

Add up to 2 parts of white spirit to 4 parts of paints (50%).

Brush or Roller

:

Add up to 2 parts of white spirit to 4 parts of paint (50%)

Conventional Spray

:

Clean all equipment with white spirit or Kerosene Immediately after use.

Cleaning

:

Smooth Glossy Finish.

Finish

:

0.91Liter, 3.64Liter , 14.56 Liter

Pack Size

#### Recommended System:

General Steel Surface/Non Ferrous

- For Non Ferrous 1 Coat of wash prime .
- 1-2 coat MOBI red oxide primer
- 2 -3 Coats MOBI Matt Enamel.

#### Recommended System:

For Masonry Surface

- One coat Mobi Wall Sealer
- 1-2 coat MOBI Wall Putty
- 2 -3 Coats MOBI Matt Enamel.

#### Recommended System:

For Wood

- 1-2 coat MOBI Undercoat White.
- 2 -3 Coats MOBI Matt Enamel.
- 

### Safety & Handling Precautions:

- Use protective equipment while application e.g. Apron, Gloves, Protective Glasses and Dust Mask.
- Ensure adequate ventilation during application.
- In case of Eye Splashes, wash with plenty of Fresh Water and consult medical advice.
- In case of skin contact, wash with plenty of water. In case of skin irritation (Sensitive Skin), obtain medical advice.
- In case of ingestion, do not induce vomiting. Drink plenty of Milk/Water and immediately consult a physician.
- Store the product below 40 °C and avoid direct sunlight for a longer period.
- As long as the container is firmly sealed; the material can be kept for 18-Months without deterioration.

Spreading rates are calculated and due allowance for loss and wastage should made. Storage stability 18 months when stored properly in original sealed container at 15-35C. The data is subject to change without notice.

## NEW MUBEEN PAINT INDUSTRIES (Pvt.) Ltd.



8-KM Khushab Road, Near Dhrema Sargodha-Pakistan.

Ph: +92-48-3710739- Cell: +92-302-8602213 - +92-344-7473646

E-mail: [info@mobipaints.com](mailto:info@mobipaints.com) Website: [www.mobipaints.com](http://www.mobipaints.com)