



Technical Data

Product: MOBI PLASTIC EMULSION

Description

MOBI PLASTIC EMULSION is an excellent quality acrylic based paint suitable for all types of interior masonry surfaces. Its a blend of selective pigments, extenders and additives. It is easy to clean, extra smooth and has a silky feel. All these attributes differentiate MOBI Plastic Emulsion from other brands available in this category.

SURFACE PREPARATION:

Surfaces must be clean, dry, free from masonry salts. Remove all defective or poorly adhering materials by rubbing down using a suitable abrasive paper or stiff brush. Treat any area affected by mould, lichens, algae or moss with bleach. Previously painted surfaces should be thoroughly rubbed down using a suitable abrasive paper and then dust off.

Filling New Surfaces:

After priming new surfaces with MOBI Interior Water Base Primer / MOBI Oil Base Primer, fill the surface with Mobi Fine Filler/Wall Putty/Care Putty. Please refer to TDS of MOBI Interior Water Base Primer / MOBI Oil Base Primer & Mobi Fine Filler/Wall Putty/Care Putty for correct application procedure and drying time properties.

Powdery, Dusty Surfaces, Defects, Cracks & Other Surfaces:

Repair minor defects. For large holes & cracks use sand and cement mixture. Allow to dry. Prime the surface with MOBI Interior Water Base Primer / MOBI Oil Base Primer and then fill any surface imperfections with the Mobi Fine Filler/Wall Putty/Care Putty. Scuff the surface using suitable abrasive paper and dust off.

TECHNICAL DATA

Composition (Nominal)

Pigment	:	Non Lead Pigment
Binder	:	Acrylic Co-Polymer
Solvent	:	Water

Solid content by volume (%)	:	65 ± 5 %
Colors	:	As per shade card
Film Thickness	:	Not Applicable
Drying Time at 25°C	:	1-2 Hours
Recoat at 25°C	:	3-4 Hours
Ph	:	8.5 – 9.5
Pack Viscosity	:	16 - 22 Poise
Specific Gravity	:	1.38 – 1.45 (Depending Upon Colors)

NEW MUBEEN PAINT INDUSTRIES (Pvt.) Ltd.



ISO 9001:2015 CERTIFIED COMPANY

8-KM Khushab Road, Near Dhrema Sargodha-Pakistan.
Ph: +92-48-3710739- Cell: +92-302-8602213 - +92-344-7473646
E-mail: info@mobipaints.com Website: www.mobipaints.com



Technical Data

Product: MOBI PLASTIC EMULSION

TECHNICAL DATA

Practical Coverage	:	A guide to the practical coverage which can be achieved under normal condition is 120 - 130 Square foot /liter/coat depending upon surface profile
Application	:	Brush,  Roller 
Thinning	:	
Brush or Roller	:	For application thinning should not exceed 2-3 parts of clean water to 4 parts of paint (50-75%).
Cleaning	:	Clean all equipment with water immediately after use.
Finish	:	Smooth Matt Finish
Pack Size	:	1 Liter, 4 Liter , 16 Liter

Recommended System: Powdery Surface

- 1coat MOBI MOBI Interior Water Base Primer / MOBI Oil Base Primer
- 2-3 coats Mobi Fine Filler/Wall Putty/Care Putty.
- MOBI Plastic Emulsion(2 or more coat)

Recommended System: Alkaline & New Surface

- 1coat MOBI Interior Water Base Primer / MOBI Oil Base Primer
- 2-3 coats Mobi Fine Filler/Wall Putty/Care Putty.
- MOBI Plastic Emulsion (2 or more coat)

Normal Sound surface previously painted:

- No Primer required.
- Mobi Fine Filler/Wall Putty/Care Putty as and where required.
- MOBI Plastic Emulsion (2 or more coat)

Safety & Handling Precautions:

- Use protective equipment while application e.g. Apron, Gloves, Protective Glasses and Dust Mask.
- Ensure adequate ventilation during application.
- In case of Eye Splashes, wash with plenty of Fresh Water and consult medical advice.
- In case of skin contact, wash with plenty of water. In case of skin irritation (Sensitive Skin), obtain medical advice.
- In case of ingestion, do not induce vomiting. Drink plenty of Milk/Water and immediately consult a physician.
- Store the product below 40 °C and avoid direct sunlight for a longer period.
- As long as the container is firmly sealed; the material can be kept for 18-Months without deterioration.

Spreading rates are calculated and due allowance for loss and wastage should made. Storage stability 18 months when stored properly in original sealed container at 15-35C. The data is subject to change without notice.

NEW MUBEEN PAINT INDUSTRIES (Pvt.) Ltd.



8-KM Khushab Road, Near Dhrema Sargodha-Pakistan.
Ph: +92-48-3710739- Cell: +92-302-8602213 - +92-344-7473646
E-mail: info@mobipaints.com Website: www.mobipaints.com