



## Technical Data

### Product: MOBI PRIMER SHEESHA PUTTY

#### Description

MOBI PRIMER SHEESHA PUTTY (water based) is a premium quality ready to use filler. It gives a smooth and brilliant white base by filling the pores. It is easy to apply and quick in drying. This putty is formulated to retain a strong adhesion on the wall surface. It provides a very strong, durable base that provides an ideal finish for subsequent coats.

#### SURFACE PREPARATION:

Allow all new surfaces to dry out completely. Surface must be clean, dry & free of all masonry salts. Remove all defective or poorly adhering materials by rubbing down using a suitable abrasive paper or stiff brush. Treat any area affected by mould, lichens, algae or moss with bleach. Previously painted surfaces should be thoroughly rubbed down using a suitable abrasive paper and then dust off.

#### New Surfaces:

Prime new surfaces with 1 coat of MOBI Interior Water Base Primer / MOBI Oil Base Primer. Please refer to TDS of MOBI Interior Water Base Primer / MOBI Oil Base Primer for correct application procedure and drying time properties.

#### Powdery, Dusty Surfaces, Defects, Cracks & Other Surfaces:

Repair minor defects. For large holes & cracks use sand and cement mixture. Allow to dry. Prime the surface with MOBI Interior Water Base Primer / MOBI Oil Base Primer before applying MOBI Primer Sheesha Putty.

#### TECHNICAL DATA

TYPE	:	Ready to use.
Composition (Nominal)		
Pigment	:	Non Lead Pigment
Binder	:	PVA Co-Polymer
Solvent	:	Water
Solid content by volume (%)	:	High solid putty
Film Thickness		
Ph	:	8.5 – 9.5
Gel Strength	:	140-160 GM/CM3 @30C
Drying Time at 25°C	:	2-3 Hours
Recoat at 25°C	:	4-6 Hours
Practical Coverage	:	A guide to the practical coverage which can be achieved under normal condition is 40-50 square Feet /Kg/coat.

## NEW MUBEEN PAINT INDUSTRIES (Pvt.) Ltd.




8-KM Khushab Road, Near Dhrema Sargodha-Pakistan.  
Ph: +92-48-3710739- Cell: +92-302-8602213 - +92-344-7473646  
E-mail: [info@mobipaints.com](mailto:info@mobipaints.com) Website: [www.mobipaints.com](http://www.mobipaints.com)



## Technical Data

Product: MOBI PRIMER SHEESHA PUTTY

### TECHNICAL DATA

Application	:	Scraper or Putty Applicator 
Thinning	:	Ready to use.
Cleaning	:	Clean all equipment with water immediately after use.
Finish	:	Smooth Matt Finish
Pack Size	:	5Kg ,20 Kg

#### Recommended System: Alkaline & New Surface

- 1coat MOBI Interior Water Base Primer / MOBI Oil Base Primer
- 2-3 coats Mobi Primer Sheesha Putty.
- 2 or more coats any of MOBI interior top coat.

#### Recommended System: Powdery Surface

- 1coat MOBI Interior Water Base Primer / MOBI Oil Base Primer
- 2-3 coats Mobi Primer Sheesha Putty..
- 2 or more coats any of MOBI interior top coat.

#### Normal Sound surface previously painted:

- No primer required.
- 2-3 coats Mobi Primer Sheesha Putty.
- where required.
- 2 or more coats any of MOBI interior top coat.

### Safety & Handling Precautions:

- Use protective equipment while application e.g. Apron, Gloves, Protective Glasses and Dust Mask.
- Ensure adequate ventilation during application.
- In case of Eye Splashes, wash with plenty of Fresh Water and consult medical advice.
- In case of skin contact, wash with plenty of water. In case of skin irritation (Sensitive Skin), obtain medical advice.
- In case of ingestion, do not induce vomiting. Drink plenty of Milk/Water and immediately consult a physician.
- Store the product below 40 °C and avoid direct sunlight for a longer period.
- As long as the container is firmly sealed; the material can be kept for 18-Months without deterioration.

Spreading rates are calculated and due allowance for loss and wastage should made. Storage stability 18 months when stored properly in original sealed container at 15-35C. The data is subject to change without notice.

## NEW MUBEEN PAINT INDUSTRIES (Pvt.) Ltd.



ISO 9001:2015 CERTIFIED COMPANY

8-KM Khushab Road, Near Dhrema Sargodha-Pakistan.  
Ph: +92-48-3710739- Cell: +92-302-8602213 - +92-344-7473646  
E-mail: [info@mobipaints.com](mailto:info@mobipaints.com) Website: [www.mobipaints.com](http://www.mobipaints.com)