



Technical Data

Product: MOBI UNDERCOAT WHITE

Description

MOBI UNDERCOAT WHITE is a high quality solvent base alkali resistant primer for sealing timber or wood surfaces. It is an excellent sealing primer, which provides good adhesion both for the surface and top coat.

SURFACE PREPARATION:

New Surface:

New surface must be clean and free from Oil, Grease and Dust.

Repaint:

Remove all defective or poorly adhering material by rubbing down using a suitable abrasive paper and dust off.

TECHNICAL DATA

Composition (Nominal)

Pigment	:	Non Lead Pigment
Binder	:	Alkyd
Solvent	:	MTT, Kerosene Oil, White Spirit

Volume solids : 50 ± 10 %

Colors : White only

Film Thickness : Wet : 50-55 micrometers.
Dry : 20-25 micrometers.

Pack Viscosity : 15 – 18 Poise

Specific Gravity : 1.45 ± 0.05

Drying Time at 25°C : 5-6 Hours

Recoat at 25°C : 16 Hours

Practical Coverage : A guide to the practical coverage which can be achieved under normal condition is 140 -170 Square foot /liter/coat.

NEW MUBEEN PAINT INDUSTRIES (Pvt.) Ltd.



ISO 9001:2015 CERTIFIED COMPANY




8-KM Khushab Road, Near Dhrema Sargodha-Pakistan.
Ph: +92-48-3710739- Cell: +92-302-8602213 - +92-344-7473646
E-mail: info@mobipaints.com Website: www.mobipaints.com



Technical Data

Product: MOBI UNDERCOAT WHITE

TECHNICAL DATA

Application	:	Brush,  Roller  Spray 
Thinning	:	
Brush or Roller	:	Add up to 2 parts of white spirit to 4 parts of paints (50%).
Conventional Spray	:	Add up to 2 parts of white spirit to 4 parts of paint (50%)
Cleaning	:	Clean all equipment with white spirit or Kerosene immediately after use.
Finish	:	Smooth Matt Finish
Pack Size	:	0.91 , 3.64 , 14.56 Liter

Recommended System:

New Surface

- 1 – 2 coats Mobi Under Coat White.
- 2 or more coats of Mobi Finishing Coat.

Normal Sound surface previously painted:

- 1 -2 coast Mobi Under Coat White if required.
- 2 or more coats of Mobi Finishing Coat.

Safety & Handling Precautions:

- Use protective equipment while application e.g. Apron, Gloves, Protective Glasses and Dust Mask.
- Ensure adequate ventilation during application.
- In case of Eye Splashes, wash with plenty of Fresh Water and consult medical advice.
- In case of skin contact, wash with plenty of water. In case of skin irritation (Sensitive Skin), obtain medical advice.
- In case of ingestion, do not induce vomiting. Drink plenty of Milk/Water and immediately consult a physician.
- Store the product below 40 °C and avoid direct sunlight for a longer period.
- As long as the container is firmly sealed; the material can be kept for 18-Months without deterioration.

Spreading rates are calculated and due allowance for loss and wastage should made. Storage stability 18 months when stored properly in original sealed container at 15-35C. The data is subject to change without notice.

NEW MUBEEN PAINT INDUSTRIES (Pvt.) Ltd.



8-KM Khushab Road, Near Dhrema Sargodha-Pakistan.
Ph: +92-48-3710739- Cell: +92-302-8602213 - +92-344-7473646
E-mail: info@mobipaints.com Website: www.mobipaints.com