



Technical Data

Product: MOBI WALL EMULSION

Description

Mobi Wall Emulsion is an excellent quality emulsion with improved coverage, binding and finish. It is specially developed for all interior surfaces including brick work, plaster, cement & wall boards.

SURFACE PREPARATION:

Surfaces must be clean, dry, free from masonry salts. Remove all defective or poorly adhering materials by rubbing down using a suitable abrasive paper or stiff brush. Treat any area affected by mould, lichens, algae or moss with bleach. Previously painted surfaces should be thoroughly rubbed down using a suitable abrasive paper and then dust off.

Filling New Surfaces:

After priming new surfaces with MOBI Interior Water Base Primer / MOBI Oil Base Primer, fill the surface with Mobi Fine Filler/Wall Putty/Care Putty. Please refer to TDS of MOBI Interior Water Base Primer / MOBI Oil Base Primer & Mobi Fine Filler/Wall Putty/Care Putty for correct application procedure and drying time properties.

Powdery, Dusty Surfaces, Defects, Cracks & Other Surfaces:

Repair minor defects. For large holes & cracks use sand and cement mixture. Allow to dry. Prime the surface with MOBI Interior Water Base Primer / MOBI Oil Base Primer and then fill any surface imperfections with the Mobi Fine Filler/Wall Putty/Care Putty. Scuff the surface using suitable abrasive paper and dust off.

TECHNICAL DATA

Composition (Nominal)

Pigment	:	Non Lead Pigment
Binder	:	PVA Co-Polymer
Solvent	:	Water

Solid content by volume (%)	:	65 ± 5 %
Colors	:	As per shade card
Film Thickness	:	Not Applicable
Drying Time at 25°C	:	1-2 Hours
Recoat at 25°C	:	3-4 Hours
Ph	:	8.5 – 9.5
Pack Viscosity	:	28 - 38 Poise
Specific Gravity	:	1.50 – 1.62 (Depending Upon Colors)
No of Coats	:	2 – 3 Coats

NEW MUBEEN PAINT INDUSTRIES (Pvt.) Ltd.



8-KM Khushab Road, Near Dhrema Sargodha-Pakistan.
Ph: +92-48-3710739- Cell: +92-302-8602213 - +92-344-7473646
E-mail: info@mobipaints.com Website: www.mobipaints.com



Technical Data

Product: MOBI WALL EMULSION

TECHNICAL DATA

Practical Coverage	:	A guide to the practical coverage which can be achieved under normal condition is 130 - 150 Square foot /liter/coat depending upon surface profile
Application	:	Brush,  Roller 
Thinning	:	
Brush or Roller	:	For application thinning should not exceed 2-3 parts of clean water to 4 parts of paint (50-75%).
Cleaning	:	Clean all equipment with water immediately after use.
Finish	:	Smooth Matt Finish
Pack Size	:	3.64 Liter , 14.56 Liter

Recommended System: Powdery Surface

- 1coat MOBI MOBI Interior Water Base Primer / MOBI Oil Base Primer
- 2-3 coats Mobi Fine Filler/Wall Putty/Care Putty.
- MOBI Wall Emulsion (2 or more coat)

Recommended System: Alkaline & New Surface

- 1coat MOBI Interior Water Base Primer / MOBI Oil Base Primer
- 2-3 coats Mobi Fine Filler/Wall Putty/Care Putty.
- MOBI Wall Emulsion (2 or more coat)

Normal Sound surface previously painted:

- No Primer required.
- Mobi Fine Filler/Wall Putty/Care Putty as and where required.
- MOBI Wall Emulsion (2 or more coat)

Safety & Handling Precautions:

- Use protective equipment while application e.g. Apron, Gloves, Protective Glasses and Dust Mask.
- Ensure adequate ventilation during application.
- In case of Eye Splashes, wash with plenty of Fresh Water and consult medical advice.
- In case of skin contact, wash with plenty of water. In case of skin irritation (Sensitive Skin), obtain medical advice.
- In case of ingestion, do not induce vomiting. Drink plenty of Milk/Water and immediately consult a physician.
- Store the product below 40 °C and avoid direct sunlight for a longer period.
- As long as the container is firmly sealed; the material can be kept for 18-Months without deterioration.

Spreading rates are calculated and due allowance for loss and wastage should made. Storage stability 18 months when stored properly in original sealed container at 15-35C. The data is subject to change without notice.

NEW MUBEEN PAINT INDUSTRIES (Pvt.) Ltd.



8-KM Khushab Road, Near Dhrema Sargodha-Pakistan.
Ph: +92-48-3710739- Cell: +92-302-8602213 - +92-344-7473646
E-mail: info@mobipaints.com Website: www.mobipaints.com