



Technical Data

Product: MOBI WALL PUTTY

Description

MOBI WALL PUTTY (water based) is a ready to use filler. It gives a smooth and brilliant white base by filling the pores. It is easy to apply and quick in drying. Its excellent filling properties give a smooth finish for topcoat application. MOBI Wall Putty is recommended to use only on interior surfaces.

SURFACE PREPARATION:

Allow all new surfaces to dry out completely. Surface must be clean, dry & free of all masonry salts. Remove all defective or poorly adhering materials by rubbing down using a suitable abrasive paper or stiff brush. Treat any area affected by mould, lichens, algae or moss with bleach. Previously painted surfaces should be thoroughly rubbed down using a suitable abrasive paper and then dust off.

New Surfaces:

Prime new surfaces with 1 coat of MOBI Interior Water Base Primer / MOBI Oil Base Primer. Please refer to TDS of MOBI Interior Water Base Primer / MOBI Oil Base Primer for correct application procedure and drying time properties.

Powdery, Dusty Surfaces, Defects, Cracks & Other Surfaces:

Repair minor defects. For large holes & cracks use sand and cement mixture. Allow to dry. Prime the surface with MOBI Interior Water Base Primer / MOBI Oil Base Primer before applying MOBI Wall Putty.

TECHNICAL DATA

TYPE	:	Ready to use.
Composition (Nominal)		
Pigment	:	Non Lead Pigment
Binder	:	PVA Co-Polymer
Solvent	:	Water
Solid content by volume (%)	:	High solid putty
Film Thickness		
Ph	:	8.5 – 9.5
Gel Strength	:	160-180 GM/CM3 @30C
Drying Time at 25°C	:	2-3 Hours
Recoat at 25°C	:	4-6 Hours
Practical Coverage	:	A guide to the practical coverage which can be achieved under normal condition is 40-50 square Feet /Kg/coat.

NEW MUBEEN PAINT INDUSTRIES (Pvt.) Ltd.




8-KM Khushab Road, Near Dhrema Sargodha-Pakistan.
Ph: +92-48-3710739- Cell: +92-302-8602213 - +92-344-7473646
E-mail: info@mobipaints.com Website: www.mobipaints.com



Technical Data

Product: MOBI WALL PUTTY

TECHNICAL DATA

Application	:	Scraper or Putty Applicator 
Thinning	:	Ready to use.
Cleaning	:	Clean all equipment with water immediately after use.
Finish	:	Smooth Matt Finish
Pack Size	:	5 Kg , 20 Kg

Recommended System:

Alkaline & New Surface

- 1coat MOBI Interior Water Base Primer / MOBI Oil Base Primer
- 2-3 coats Mobi Wall Putty.
- 2 or more coats any of MOBI interior top coat.

Recommended System:

Powdery Surface

- 1coat MOBI Interior Water Base Primer / MOBI Oil Base Primer
- 2-3 coats Mobi Wall Putty.
- 2 or more coats any of MOBI interior top coat.

Normal Sound surface previously

painted:

- No primer required.
- 2-3 coats MOBI Wall Putty where required.
- 2 or more coats any of MOBI interior top coat.

Safety & Handling Precautions:

- Use protective equipment while application e.g. Apron, Gloves, Protective Glasses and Dust Mask.
- Ensure adequate ventilation during application.
- In case of Eye Splashes, wash with plenty of Fresh Water and consult medical advice.
- In case of skin contact, wash with plenty of water. In case of skin irritation (Sensitive Skin), obtain medical advice.
- In case of ingestion, do not induce vomiting. Drink plenty of Milk/Water and immediately consult a physician.
- Store the product below 40 °C and avoid direct sunlight for a longer period.
- As long as the container is firmly sealed; the material can be kept for 18-Months without deterioration.

Spreading rates are calculated and due allowance for loss and wastage should made. Storage stability 18 months when stored properly in original sealed container at 15-35C. The data is subject to change without notice.

NEW MUBEEN PAINT INDUSTRIES (Pvt.) Ltd.



ISO 9001:2015 CERTIFIED COMPANY

8-KM Khushab Road, Near Dhrema Sargodha-Pakistan.
Ph: +92-48-3710739- Cell: +92-302-8602213 - +92-344-7473646
E-mail: info@mobipaints.com Website: www.mobipaints.com