



## Technical Data

**Product: MOBI WEATHER PLUS**

### Description

**MOBI WEATHER PLUS** is high quality acrylic based emulsion paint for new or previously painted exterior masonry surfaces. Because of its outstanding resistance to weathering, it is perfect for protection, decoration and long lasting finish of all masonry surfaces such as brick work, plaster and cement rendering.

### SURFACE PREPARATION:

Surfaces must be clean, dry, free from masonry salts. Remove all defective or poorly adhering materials by rubbing down using a suitable abrasive paper or stiff brush. Treat any area affected by mould, lichens, algae or moss with bleach. Previously painted surfaces should be thoroughly rubbed down using a suitable abrasive paper and then dust off.

### Filling New Surfaces:

After priming new surfaces with MOBI Interior & Exterior Primer / MOBI Exterior Primer, fill the surface if required with Mobi Exterior Fine Filler. Please refer to TDS of MOBI Interior MOBI Interior & Exterior Primer / MOBI Exterior Primer & Mobi Exterior Fine Filler for correct application procedure and drying time properties.

### Powdery, Dusty Surfaces, Defects, Cracks & Other Surfaces:

Repair minor defects. For large holes & cracks use sand and cement mixture. Allow to dry. Prime the surface with MOBI Interior & Exterior Primer / MOBI Exterior Primer and then fill any surface imperfections with the Mobi Exterior Fine Filler. Scuff the surface using suitable abrasive paper and dust off.

### TECHNICAL DATA

#### **Composition (Nominal)**

Pigment	:	Non Lead Pigment
Binder	:	Acrylic Co-Polymer
Solvent	:	Water

<b>Solid content by volume (%)</b>	:	65 ± 5 %
<b>Colors</b>	:	As per shade card
<b>Film Thickness</b>	:	Not Applicable
<b>Drying Time at 25°C</b>	:	1-2 Hours
<b>Recoat at 25°C</b>	:	3-4 Hours
<b>Ph</b>	:	8.5 – 9.5
<b>Pack Viscosity</b>	:	16 - 22 Poise
<b>Specific Gravity</b>	:	1.36 – 1.5 (Depending Upon Colors)
<b>No of Coats</b>	:	3 – 4 Coats

## NEW MUBEEN PAINT INDUSTRIES (Pvt.) Ltd.





8-KM Khushab Road, Near Dhrema Sargodha-Pakistan.  
Ph: +92-48-3710739- Cell: +92-302-8602213 - +92-344-7473646  
E-mail: [info@mobipaints.com](mailto:info@mobipaints.com) Website: [www.mobipaints.com](http://www.mobipaints.com)



## Technical Data

Product: MOBI WEATHER PLUS

### TECHNICAL DATA

<b>Practical Coverage</b>	:	A guide to the practical coverage which can be achieved under normal condition is 130 - 150 Square foot /liter/coat depending upon surface profile.
<b>Application</b>	:	Brush,  Roller 
<b>Thinning</b>	:	
<b>Brush or Roller</b>	:	For application thinning should not exceed 2-3 parts of clean water to 4 parts of paint (50-75%).
<b>Cleaning</b>	:	Clean all equipment with water immediately after use.
<b>Finish</b>	:	Smooth Matt Finish
<b>Pack Size</b>	:	1 Liter, 4 Liter , 16 Liter

#### Recommended System: Powdery Surface

- 1coat MOBI Interior & Exterior Primer / MOBI Exterior Primer.
- 1 thin coat Mobi Exterior Fine Filler.
- MOBI Weather Plus(2 or more coat)

#### Recommended System: Alkaline & New Surface

- 1coat MOBI Interior & Exterior Primer / MOBI Exterior Primer.
- 1 thin coat Mobi Exterior Fine Filler.
- MOBI Weather Plus (2 or more coat)

#### Normal Sound surface previously painted:

- No Primer required.
- 1 thin coat Mobi Exterior Fine Filler if and where required.
- MOBI Weather Plus (2 or more coat)

### Safety & Handling Precautions:

- Use protective equipment while application e.g. Apron, Gloves, Protective Glasses and Dust Mask.
- Ensure adequate ventilation during application.
- In case of Eye Splashes, wash with plenty of Fresh Water and consult medical advice.
- In case of skin contact, wash with plenty of water. In case of skin irritation (Sensitive Skin), obtain medical advice.
- In case of ingestion, do not induce vomiting. Drink plenty of Milk/Water and immediately consult a physician.
- Store the product below 40 °C and avoid direct sunlight for a longer period.
- As long as the container is firmly sealed; the material can be kept for 18-Months without deterioration.

Spreading rates are calculated and due allowance for loss and wastage should made. Storage stability, 18 Months when stored properly in original sealed container at 15-35C. The data is subject to change without notice.

## NEW MUBEEN PAINT INDUSTRIES (Pvt.) Ltd.



8-KM Khushab Road, Near Dhrema Sargodha-Pakistan.  
Ph: +92-48-3710739- Cell: +92-302-8602213 - +92-344-7473646  
E-mail: [info@mobipaints.com](mailto:info@mobipaints.com) Website: [www.mobipaints.com](http://www.mobipaints.com)