



## Technical Data

### Product: MOBI WOOD SEALER

#### Description

**MOBI WOOD SEALER** is an NC based premium quality sealer for wood and wood care products. It is an ideal sealer to fill surface imperfections of all kinds of wooden furniture and fixtures. It penetrates into the pores of wood and prevents sinkage of topcoat to allow good hold out.

#### SURFACE PREPARATION:

Ensure that the wood is dry right through and properly seasoned. Fill the imperfections, grooves, cuts etc. with the filler by matching its color with that of the wood. Thoroughly scuff with coarse abrasive paper to produce a uniform surface. Level out all the surface rock bottom with manual sanding or by using mechanical sander. Thin MOBI Wood Sealer with MOBI Thinner Special. Mix thoroughly and apply two or more coats depending upon surface condition. Allow a gap of 30 minutes in between coats. Let it dry for 3- 4 hours. Scuff the surface with fine sand paper, dust off and petrol wipe before over coating with MOBI Wood Lacquer.

#### TECHNICAL DATA

TYPE	:	Single Pack.
Flash Point	:	< 21°C
Specific Gravity	:	0.95 ± 0.05
Color	:	Milky & Pale Yellow
Thinning	:	50% to 75% with Mobi Thinner Special
Average Spreading Rate	:	100 ~ 110 Sq. Feet per liter per coat.
Drying Time	:	a. Surface Dry: 10 - 20 minutes @ 30°C b. Recoat : 30 minutes @ 30°C c. Hard Dry : 3 Hours
Application	:	Spray
Number of Coats	:	3 ~ 4 Coats
Finish & Gloss	:	Smooth, Matt
Thinner	:	Mobi Thinner Special
Packing	:	0.91, 3.64 Liter

#### Safety & Handling Precautions:

- Use protective equipment while application e.g. Apron, Gloves, Protective Glasses and Dust Mask.
- Ensure adequate ventilation during application.
- In case of Eye Splashes, wash with plenty of Fresh Water and consult medical advice.
- In case of skin contact, wash with plenty of water. In case of skin irritation (Sensitive Skin), obtain medical advice.
- In case of ingestion, do not induce vomiting. Drink plenty of Milk/Water and immediately consult a physician.
- Store the product below 40 °C and avoid direct sunlight for a longer period.
- As long as the container is firmly sealed; the material can be kept for 18-Months without deterioration.

Spreading rates are calculated and due allowance for loss and wastage should made. Storage stability 18 months when stored properly in original sealed container at 15-35C. The data is subject to change without notice.

## NEW MUBEEN PAINT INDUSTRIES (Pvt.) Ltd.



8-KM Khushab Road, Near Dhrema Sargodha-Pakistan.  
Ph: +92-48-3710739- Cell: +92-302-8602213 - +92-344-7473646  
E-mail: [info@mobipaints.com](mailto:info@mobipaints.com) Website: [www.mobipaints.com](http://www.mobipaints.com)